



Note! Changed technical specification! See data sheet/declaration of compliance with the order  
Pneumatic timing relay block ON delay 1 ... 60 s 1 NO + 1 NC, for motor contactors size S0 according to DIN VDE 0116 !!! Phased-out product !!!

### General technical data

Product brand name		SIRIUS
Product designation		pneumatic delay block
Design of the product		slow-operating
Size of contactor		S0
Ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	5 ... 50
Protection class IP on the front		IP20
Mechanical service life (switching cycles) typical		5 000 000
Electrical endurance (switching cycles) at AC-15 at 230 V typical		1 000 000
Mechanical service life (switching cycles)		
• with 3RT2.2 contactor		5 000 000
Adjustable pickup delay time	s	60 ... 1
Insulation voltage with degree of pollution 3 at AC rated value	V	690
Relative accuracy of the operating delay time/backslide delay time related to setting value	%	20

## Auxiliary circuit

### Operating current

• of auxiliary contacts		
— at AC-12 maximum	A	10
— at AC-14		
— at 230 V	A	6
— at 400 V	A	4
— at 500 V	A	2.5
— at 690 V	A	1.5
— at AC-15		
— at 230 V	A	6
— at 400 V	A	4
— at DC-13		
— at 24 V	A	4
— at 48 V	A	2
— at 110 V	A	0.7
— at 220 V	A	0.3
— at 440 V	A	0.1
• at AC-15		
— at 500 V rated value	A	2.5
— at 690 V rated value	A	1.5

## Short-circuit protection

**Design of the fuse link for short-circuit protection of the auxiliary switch required**

Fuse gG 10 A with short-circuit current  $I_k = 1 \text{ kA}$  according to IEC 60947-5-1

## Installation/ mounting/ dimensions

<b>Mounting type</b>		clip-on
<b>Width</b>	mm	45
<b>Height</b>	mm	44.6
<b>Depth</b>	mm	83.5
<b>Mounting position</b>		any

## Connections/ Terminals

Type of electrical connection for auxiliary and control current circuit

screw-type terminals

### Type of connectable conductor cross-sections

• for auxiliary contacts		
— solid		2x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 4 mm <sup>2</sup> )
— finely stranded		
— with core end processing		2x (0.5 ... 2.5 mm <sup>2</sup> )
• at AWG conductors for auxiliary contacts		2x (22 ... 12)

## Certificates/ approvals

Certificate of suitability

CE / UL / CSA / CCC

General Product Approval

EMC

Declaration of  
Conformity



CCC



TÜV



UL



RCM



EG-Konf.

Declaration of  
Conformity

Shipping Approval

other

[Miscellaneous](#)



[Confirmation](#)



VDE

Safety related data

Protection against electrical shock

finger-safe

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2926-2PA11-0MT0>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2926-2PA11-0MT0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2926-2PA11-0MT0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2926-2PA11-0MT0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2926-2PA11-0MT0&lang=en)





last modified:

09/23/2020