

SIPLUS LOGO! 12/24RCE -20 ... +70°C start up -20°C with conformal coating based on 6ED1052-1MD08-0BA0 . Logikmodul, Display SV/E/A: 24V/24V/24V trans., 8DE (4AE)/4DA, SP. 400 blocks, modular erweiterbar, Ethernet integr. Web-Server, Datalog, benutzerdefinierte Web-Seiten, Standard microSD-Karte für LOGO! Soft Comfort ab V8, ältere Projekte ablauffähig



Figure similar

Display	
with display	Yes; The legibility and response time of the display may be reduced or lengthened at temperatures outside 0 ... +55 °C. These effects are self-reversing on return to the normal temperature range of 0 ... +55 °C.
Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
Rated value (DC)	
• 12 V DC	Yes
• 24 V DC	Yes
permissible range, lower limit (DC)	10.8 V
permissible range, upper limit (DC)	28.8 V
Time of day	
Time switching clocks	
• Number	400; Max. 400, function-specific

- Power reserve

480 h

Digital inputs

Number of digital inputs 8; Of which 4 can be used in analog mode (0 to 10 V)

Digital outputs

Number of digital outputs 4; Relays

Short-circuit protection No; external fusing necessary

Output current

- for signal "1" permissible range for 0 to 55 °C, max. 10 A

Relay outputs

Switching capacity of contacts

- with inductive load, max. 3 A
- with resistive load, max. 10 A

EMC

Emission of radio interference acc. to EN 55 011

- Limit class B, for use in residential areas Yes

Ambient conditions

Ambient temperature during operation

- min. -25 °C; = Tmin; Startup @ -20 °C
- max. 70 °C; Tmax; Tmax > +55 °C max. load 1 A per relay or max. load 3 A per relay and half the number of DIs (no adjacent points)
- At cold restart, min. -20 °C; incl. condensation / frost permitted (no commissioning under condensation conditions)

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m
- Ambient air temperature-barometric pressure-altitude Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max. 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation

Resistance

Coolants and lubricants

- Resistant to commercially available coolants and lubricants Yes; Incl. diesel and oil droplets in the air

Use in stationary industrial systems

- to biologically active substances according to EN 60721-3-3 Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request

— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *

Use on ships/at sea

— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *

Usage in industrial process technology

— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

Remark

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
---	--

Conformal coating

• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A

Dimensions

Width	71.5 mm
Height	90 mm
Depth	60 mm

last modified: 10/05/2020