## **SIEMENS**

## Data sheet

## 6GK5008-0BA10-1AB2

SCALANCE XB008 Unmanaged Industrial Ethernet Switch for 10/100 Mbit/s for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 8x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download



| product type designation   | SCALANCE XB008        |  |
|--|-----------------------|--|
| transfer rate  |                       |  |
| transfer rate  | 10 Mbit/s, 100 Mbit/s |  |
| interfaces / for communication / integrated                      |                       |  |
| number of electrical connections                                 |                       |  |
| <ul> <li>for network components or terminal equipment</li> </ul> | 8; RJ45               |  |
| number of 100 Mbit/s SC ports                                    |                       |  |
| • for multimode  | 0                     |  |
| interfaces / other   |                       |  |
| number of electrical connections                                 |                       |  |
| <ul> <li>for power supply</li> </ul>                             | 1                     |  |
| type of electrical connection                                    |                       |  |
| <ul> <li>for power supply</li> </ul>                             | 3-pole terminal block |  |
| supply voltage, current consumption, power loss                  |                       |  |
| type of voltage / 1 / of the supply voltage                      | DC                    |  |
| <ul> <li>supply voltage / 1 / rated value</li> </ul>             | 24 V                  |  |
| • power loss [W] / 1 / rated value                               | 2.88 W                |  |

| <ul> <li>supply voltage / 1 / rated value</li> </ul>                                      | 19.2 28.8 V  |
|---|--|
| <ul> <li>consumed current / 1 / maximum</li> </ul>  | 0.12 A   |
| <ul> <li>product component / 1 / fusing at power supply</li> </ul>                        | Yes  |
| input   |  |
| type of voltage / 2 / of the supply voltage   |  |
| <ul> <li>supply voltage / 2 / rated value</li> </ul>                                      | 19.2 28.8 V  |
| ambient conditions  |  |
| ambient temperature   |  |
| <ul> <li>during operation</li> </ul>  | -10 +60 °C   |
| <ul> <li>during storage</li> </ul>  | -40 +80 °C   |
| • during transport  | -40 +80 °C   |
| relative humidity   |  |
| <ul> <li>at 25 °C / without condensation / during</li> </ul>                              | 95 %   |
| operation / maximum   |  |
| protection class IP   | IP20   |
| design, dimensions and weights  |  |
| design  | Box  |
| width   | 45 mm  |
| height  | 100 mm   |
| depth   | 87 mm  |
| net weight  | 0.18 kg  |
| mounting type   |  |
| <ul> <li>35 mm DIN rail mounting</li> </ul>   | Yes  |
| wall mounting   | Yes  |
| • S7-1500 rail mounting   | No   |
| product functions / management, configuration, eng  | aineering  |
| product function  |  |
| • multiport mirroring   | No   |
| • CoS   | Yes  |
| PROFINET conformity class   | A  |
| product function / switch-managed   | No   |
| product functions / redundancy  |  |
| product function  |  |
| <ul> <li>Parallel Redundancy Protocol (PRP)/operation<br/>in the PRP-network</li> </ul>   | Yes  |
| <ul> <li>Parallel Redundancy Protocol<br/>(PRP)/Redundant Network Access (RNA)</li> </ul> | No   |
| standards, specifications, approvals  |  |
| standard  |  |
| • for FM  | FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4 |
|   |  |

| <ul> <li>for hazardous zone</li> </ul>                                  | EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc,<br>KEMA 07ATEX0145 X   |
|---|--|
| <ul> <li>for safety / from CSA and UL</li> </ul>                        | UL 60950-1, CSA C22.2 No. 60950-1  |
| <ul> <li>for emitted interference</li> </ul>                            | EN 61000-6-4 (Class A)   |
| • for interference immunity   | EN 61000-6-2   |
| MTBF  | 214 у  |
| standards, specifications, approvals / CE                               |  |
| certificate of suitability / CE marking                                 | Yes  |
| standards, specifications, approvals / other                            |  |
| certificate of suitability  | EN 61000-6-2, EN 61000-6-4   |
| • C-Tick  | Yes  |
| <ul> <li>KC approval</li> </ul>   | Yes  |
| further information / internet-Links                                    |  |
| Internet-Link   |  |
| <ul> <li>to website: Selector SIMATIC NET<br/>SELECTION TOOL</li> </ul> | http://www.siemens.com/snst  |
| <ul> <li>to website: Industrial communication</li> </ul>                | http://www.siemens.com/simatic-net   |
| • to website: Industry Mall   | https://mall.industry.siemens.com  |
| <ul> <li>to website: Information and Download Center</li> </ul>         | http://www.siemens.com/industry/infocenter   |
| <ul> <li>to website: Image database</li> </ul>                          | http://automation.siemens.com/bilddb   |
| <ul> <li>to website: CAx Download Manager</li> </ul>                    | http://www.siemens.com/cax   |
| <ul> <li>to website: Industry Online Support</li> </ul>                 | https://support.industry.siemens.com   |
| security information  |  |
| security information  | Siemens provides products and solutions with industrial security<br>functions that support the secure operation of plants, solutions,<br>machines, equipment and/or networks. They are important<br>components in a holistic industrial security concept. With this in<br>mind, Siemens' products and solutions undergo continuous<br>development. Siemens recommends strongly that you regularly<br>check for product updates. For the secure operation of Siemens<br>products and solutions, it is necessary to take suitable preventive<br>action(e.g. cell protection concept) and integrate each component<br>into a holistic, state-of-the-art industrial security concept. Third- |

last modified:

09/30/2020

party products that may be in use should also be considered. For

http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific

more information about industrial security, visit

http://support.automation.siemens.com. (V3.4)

newsletter. For more information, visit