SIEMENS

Data sheet

3SB2455-1B



Contact block and lampholder 1 NO, Wedge base W2 x 4.6 d, soldering pin connection

Figure similar

product brand name	SIRIUS
product designation	contact block and lampholder
product type designation	- 3SB2
Contact block/ lampholder	
socket design	W2 x 4.6d
number of lampholders	1
General technical data	
product function positive opening	No
product component	
light source	No
suitability for integration	pushbutton / selector button
type of voltage	
 of the operating voltage 	AC/DC
protection class IP	
of the enclosure	IP40
of the terminal	IP00
vibration resistance acc. to IEC 60068-2-6	20 200 Hz: 5g
reference code acc. to IEC 81346-2	S
 operating voltage at AC 	
— at 50 Hz rated value	5 60 V
— at 60 Hz rated value	5 60 V
 operating voltage at DC rated value 	5 60 V
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
operational current at AC-12	
 at 24 V rated value 	10 A
 at 60 V rated value 	10 A
 at 110 V rated value 	10 A
 at 230 V rated value 	10 A
operational current at AC-15	
• at 24 V rated value	4 A
 at 110 V rated value 	4 A
• at 230 V rated value	4 A
operational current at DC-12	

	Declaration of Conformity
EHC	<u>Miscellaneous</u>

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2455-1B

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2455-1B

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2455-1B&lang=en

last modified:

11/4/2020 🖸