

product type designation	IE FC TP Marine Cable 2 x 2 (Type B)
product description	Halogen-free bus cable acc. to IEC 60754-1/2 (4-core), sold by the meter, unassembled Industrial Ethernet FC TP Marine Cable, TP installation cable for connection to FC outlet RJ45, shipbuilding certified, 4-core, shielded CAT 5, sold by the meter, delivery unit max. 1000 m, minimum order 20 m
suitability for use	For marine and offshore use
cable designation	L-9YH (ST) CH 2 x 2 x 0,34/1,5-100 GN VZN FRNC SF/UTP
electrical data	
attenuation factor per length	
• at 10 MHz / maximum	0.06 dB/m
• at 100 MHz / maximum	0.22 dB/m
impedance	
• at 1 MHz ... 100 MHz	100 Ω
relative symmetrical tolerance	
• of the characteristic impedance at 1 MHz ... 100 MHz	15 %
near-end crosstalk per length	
• at 1 MHz ... 100 MHz	0.5 dB/m
transfer impedance per length / at 10 MHz	10 mΩ/m
loop resistance per length / maximum	120 mΩ/m
operating voltage	
• RMS value	80 V
NVP value in percent	66 %
mechanical data	
number of electrical cores	4
design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tinned copper wires
type of electrical connection / FastConnect	Yes
core diameter	
• of AWG22 insulated conductor	0.75 mm
outer diameter	
• of inner conductor	0.75 mm
• of the wire insulation	1.5 mm
• of the inner sheath of the cable	3.9 mm
• of cable sheath	6.5 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
material	
• of the wire insulation	PP
• of the inner sheath of the cable	FRNC
• of cable sheath	FRNC
color	
• of the insulation of data wires	white/yellow/blue/orange
• of cable sheath	green
bending radius	
• with single bend / minimum permissible	39 mm
• with multiple bends / minimum permissible	97.5 mm
tensile load / maximum	150 N
weight per length	68 kg/km
ambient conditions	

ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport during installation note 	-25 ... +70 °C -40 ... +85 °C -40 ... +85 °C 0 ... 50 °C Electrical properties measured at 20 °C, tests according to DIN VDE 0472
ambient condition / for operation	Temperature range for permanent installation -40 °C to 85 °C
fire behavior	flame resistant according to IEC 60332-3-22 (Category A/F), smoke density according to IEC 61034-1/2
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
<ul style="list-style-type: none"> to mineral oil to grease to water 	conditional resistance, IEC 60811-2-1 (4 hours / 70 °C) Conditional resistance conditional resistance
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> halogen-free silicon-free 	Yes Yes
wire length / for Industrial Ethernet	
<ul style="list-style-type: none"> with 100BaseTX 	85 m
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; cULus / CMG / PLTC / Sun Res
UL/ETL style / 600 V Rating	No
certificate of suitability	
<ul style="list-style-type: none"> EAC approval CE marking RoHS conformity 	Yes Yes Yes
standard for structured cabling	Cat5e
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) French marine classification society (BV) Det Norske Veritas (DNV) Germanische Lloyd (GL) Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) Polski Rejestr Statkow (PRS) 	Yes Yes Yes Yes Yes No No
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	1/20/2021 