## SIEMENS

## Data sheet

product brand name

## 3SB2455-1E



Contact block and lampholder 1 NO, 1 NO, Wedge base W2 x 4.6 d, soldering pin connection

product brand name	51(105
product designation	contact block and lampholder
product type designation	3SB2
Contact block/ lampholder	
socket design	W2 x 4.6d
number of lampholders	1
General technical data	
product function positive opening	No
product component	
light source	No
suitability for integration	pushbutton / selector button
type of voltage	
<ul> <li>of the operating voltage</li> </ul>	AC/DC
protection class IP	
<ul> <li>of the enclosure</li> </ul>	IP40
<ul> <li>of the terminal</li> </ul>	IP00
vibration resistance acc. to IEC 60068-2-6	20 200 Hz: 5g
reference code acc. to IEC 81346-2	S
<ul> <li>operating voltage at AC</li> </ul>	
— at 50 Hz rated value	5 60 V
— at 60 Hz rated value	5 60 V
<ul> <li>operating voltage at DC rated value</li> </ul>	5 60 V
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	2
number of CO contacts for auxiliary contacts	0
operational current at AC-12	
• at 24 V rated value	10 A
at 60 V rated value	10 A
• at 110 V rated value	10 A
at 230 V rated value	10 A
operational current at AC-15	

SIRIUS

at 24 V rated valueat 110 V rated value

• at 230 V rated value

operational current at DC-12

4 A

4 A

4 A

<ul> <li>at 24 V rated</li> <li>at 60 V rated</li> </ul>	value					
<ul> <li>at 60 V rated</li> </ul>	value		6 A			
	value		5 A			
<ul> <li>at 110 V rated</li> </ul>	l value		2.5 A			
at 230 V rated value			1 A			
operational curren	t at DC-13					
<ul> <li>at 24 V rated</li> </ul>	value		3 A			
• at 60 V rated value			1.2 A			
• at 110 V rated value		0.7 A				
• at 230 V rated value			0.3 A			
onnections/ Termi	nals					
type of electrical connection			solder pin	connectors		
mbient conditions						
<ul> <li>ambient temperature during operation</li> </ul>			-25 +60	°C		
	erature during storage		-40 +80	°C		
stallation/ mountir						
fastening method			clip-on			
height			19 mm			
width			18 mm			
depth			29 mm			
ertificates/ approva	als					
General Product A		-			rnr	Conformity Miscellaneous
	(me	(me)				
S.				Ű	EHC	
Declaration of Conformity	other	CCC		Ű	LHL	
		ccc		Ű	LHL	
	other	CCC		Ű	LHL	
Conformity	other	CCC		Ű	LHL	

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2455-1E

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2455-1E

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SB2455-1E&lang=en

last modified:

8/19/2020 🖸