SIEMENS

Data sheet 6GK5908-0PB00

product type designation

product description



KEY-PLUG SINEMA RC

Removable medium for activating SINEMA RC for SCALANCE M-800 / S615 and for simple device replacement in the event of a fault

KEY-PLUG SINEMA RC, Removable data storage medium for enabling of the connection to SINEMA Remote Connect for S615 and SCALANCE M for simple device replacement in event of fault and for Recording of configuration data

suitability for use	Activation of SINEMA RC
ambient conditions	
ambient temperature	
during operation	-40 +75 °C
 during storage 	-40 +80 °C
 during transport 	-40 +80 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
width	24.3 mm
height	17 mm
depth	8.1 mm
net weight	5 g
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	Yes
product features, product functions, product components / general	
storage capacity	256 Mibyte
standards, specifications, approvals	
reference code	
 according to IEC 81346-2:2019 	CFA
further information / internet-Links	
Internet-Link	
 to website: TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/snst
to the website: IWLAN	http://www.siemens.com/iwlan
 to website: Industrial communication 	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com 12/18/2020 🖸
last modified:	