

product type designation



CP 5612

Communications processor CP 5612 PCI card for connection connection of a PG or PC with PCI bus to PROFIBUS or MPI usable in 32 bit and 64 bit operating systems see also entry ID 22611503

transfer rate	
transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of electrical connections	
• at the 1st interface / acc. to PROFIBUS	1
type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS 485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	
• 1 / from backplane bus	3.3 V
• 2 / from backplane bus	12 V
relative symmetrical tolerance / at DC	
• at 3.3 V	9 %
• at 12 V	8 %
consumed current	
• 1 / from backplane bus / at DC / maximum	0.15 A
• 2 / from backplane bus / at DC / maximum	0.25 A
power loss [W]	3.5 W
ambient conditions	
ambient temperature	
• during operation	5 ... 55 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP00
design, dimensions and weights	
module format	PCI
width	18 mm
height	107 mm
depth	125 mm
net weight	98 g
product features, product functions, product components / general	
number of plug-in cards of same design / plug-in / per PC	1

station	
number of units / note	-
performance data	
performance data / open communication	
software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50
performance data / PROFIBUS DP	
software / for DP master function / required	Yes, SOFTNET-PB DP
service / as DP master	
• DPV0	Yes
• DPV1	Yes
• DPV2	No
number of DP slaves / on DP master / operable	64
data volume	
• of the address range of the inputs / as DP master / total	14640 byte
• of the address range of the outputs / as DP master / total	14640 byte
• of the address range of the inputs / per DP slave	244 byte
• of the address range of the outputs / per DP slave	244 byte
• of the address range of the diagnostic data / per DP slave	244 byte
software / for DP slave function / required	Yes, SOFTNET-PB DP slave
service / as DP slave	
• DPV0	Yes
• DPV1	No
data volume	
• of the address range of the inputs / as DP slave / total	122 byte
• of the address range of the outputs / as DP slave / total	122 byte
performance data / S7 communication	
software / for S7 communication / required	Yes, SOFTNET-PB S7
number of possible connections / for S7/PG communication / maximum	8
performance data / multi-protocol mode	
number of configurable connections / per PC station	207
product functions / management, configuration, engineering	
configuration software / required	Included in the scope of delivery of the required software product
product functions / diagnostics	
product function	
• port diagnostics	Yes
standards, specifications, approvals	
standard	
• for EMC	89/336/EEC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1, UL 1950
• for emitted interference	EN 61000-6-3
• for interference immunity	EN 61000-6-2
certificate of suitability	
• CE marking	Yes
• C-Tick	Yes
accessories	
accessories	optional: MPI cable
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/industrial-controls/mall>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

12/16/2020 