

product type designation



RF160C communication module

***** spare part ***** RFID communication module RF160C for PROFIBUS DP-V0; 2 readers can be connected; without connection block for PROFIBUS

suitability for operation

PROFIBUS network according to DP-V0 together with RF200/300/600, MOBY D/U

transfer rate

transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s

interfaces

design of the interface / for point-to-point connection	RS422
number of readers / connectable	2
type of electrical connection	
• of the PROFIBUS interface	(according to the connection block)
• for supply voltage	(according to the connection block)
design of the interface / to the reader / for communication	M12, 8-pin

mechanical data

material	Thermoplastic (Valox 467, fiberglass reinforced)
color	IP Basic 714
tightening torque / of the screw for securing the equipment / maximum	3 N·m

supply voltage, current consumption, power loss

supply voltage	
• at DC / rated value	24 V
• at DC	20 ... 30 V
consumed current / at DC / at 24 V	
• without connected devices / typical	0.08 A
• with connected devices / maximum	0.85 A

ambient conditions

ambient temperature	
• during operation	0 ... 55 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
protection class IP	IP67
shock resistance	According to IEC 61131-2
shock acceleration	300 m/s ²
vibrational acceleration	100 m/s ²

design, dimensions and weights

width	60 mm
height	30 mm

depth	210 mm
net weight	0.21 kg
fastening method	2 x M5 screws
wire length / for RS 422 interface / maximum	1000 m
product features, product functions, product components / general	
display version	4 LEDs per reader connection, 4 LEDs for device status
product function / addressable transponder file handler	No
protocol / is supported	
• PROFIBUS DP-V0 protocol	Yes
• PROFIBUS DP-V1 protocol	No
product functions / management, configuration, engineering	
type of parameterization	GSD
type of programming	FC 44
type of computer-switched communication	Cyclic communication
standards, specifications, approvals	
certificate of suitability	CE, FCC, cULus
MTBF	122 y
accessories	
accessories	Connection block for ECOFAST system or M12, 7/8"
further information / internet-Links	
Internet-Link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4)

last modified:

12/16/2020 