



key-operated switch Siemens, 22 mm, round, plastic with metal front ring, lock no. LSG1, with 2 keys, 2 switch positions O-I, latching, actuating angle 90°, 10:30h/13:30h, key removal O, with laser labeling, lower case

|  |  |
|--|--|
| <b>product brand name</b>                              | SIRIUS ACT                                 |
| <b>product designation</b>                             | Key-operated switches                      |
| <b>design of the product</b>                           | Actuating/signaling element                |
| <b>product type designation</b>                        | 3SU1                                       |
| <b>product line</b>                                    | Plastic with metal front ring, matt, 22 mm |
| <b>manufacturer's article number of included key</b>   | <a href="#">3SU1950-0FN80-0AA0</a>         |
| <b>Actuator</b>  |  |
| <b>principle of operation of the actuating element</b> | latching, 90° (10:30 h/13:30 h)            |
| <b>product extension optional light source</b>         | No   |
| <b>color</b>   |  |
| • of the actuating element                             | silver                                     |
| <b>material of the actuating element</b>               | metal                                      |
| <b>shape of the actuating element</b>                  | Key  |
| <b>outer diameter of the actuating element</b>         | 29.5 mm                                    |
| <b>marking of the actuating element</b>                | Any inscription, text in lower case        |
| <b>number of switching positions</b>                   | 2  |
| <b>switch position for key distraction</b>             | O  |
| <b>actuating angle</b>                                 |  |
| • clockwise  | 90°  |
| <b>lock make</b>                                       | CES  |
| <b>key number</b>                                      | LSG1                                       |
| <b>Front ring</b>                                      |  |
| <b>product component front ring</b>                    | Yes  |
| <b>design of the front ring</b>                        | Standard                                   |
| <b>material of the front ring</b>                      | Metal, matt                                |
| <b>color of the front ring</b>                         | sand gray                                  |
| <b>General technical data</b>                          |  |
| <b>protection class IP</b>                             | IP66, IP67, IP69(IP69K)                    |
| • of the terminal                                      | IP20                                       |
| <b>degree of protection NEMA rating</b>                | 1, 2, 3, 3R, 4, 4X, 12, 13                 |
| <b>shock resistance</b>                                |  |
| • acc. to IEC 60068-2-27                               | Sinusoidal half-wave 50g / 11 ms           |
| • for railway applications acc. to DIN EN 61373        | Category 1, Class B                        |
| <b>vibration resistance</b>                            |  |
| • acc. to IEC 60068-2-6                                | 10 ... 500 Hz: 5g                          |
| • for railway applications acc. to DIN EN 61373        | Category 1, Class B                        |
| <b>operating frequency maximum</b>                     | 1 800 1/h                                  |

|  |   |
|--|---|
| mechanical service life (switching cycles) typical   | 1 000 000   |
| reference code acc. to IEC 81346-2   | S   |
| <b>Ambient conditions</b>  |   |
| <ul style="list-style-type: none"> <li>ambient temperature during operation</li> <li>ambient temperature during storage</li> </ul> | -25 ... +70 °C<br>-40 ... +80 °C                                    |
| environmental category during operation acc. to IEC 60721  | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %) |
| <b>Installation/ mounting/ dimensions</b>  |   |
| height   | 29.5 mm   |
| width  | 29.5 mm   |
| shape of the installation opening  | round   |
| mounting diameter  | 22.3 mm   |
| positive tolerance of installation diameter  | 0.4 mm  |
| mounting height  | 61 mm   |
| installation width   | 29.5 mm   |
| installation depth   | 25.4 mm   |
| <b>Certificates/ approvals</b>   |   |
| <b>Further information</b>   |   |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1030-5HF01-0AA0-Z Y12>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1030-5HF01-0AA0-Z Y12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1030-5HF01-0AA0-Z Y12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1030-5HF01-0AA0-Z Y12&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1030-5HF01-0AA0-Z Y12&lang=en)

last modified:

2/1/2021 