

USB keyboard INT for 16:9 PRO devices, in stainless steel, RAL9006 (silver), with numerical keypad, inclination adjustable Further information, Quantity and content: see technical data



General information	
Product type designation	Stainless steel keyboard
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> • Design • Keyboard assignment • Color of the buttons • Color of the key inscription • Key illumination • Function keys <ul style="list-style-type: none"> — Number of function keys • Number pad • status LED displays <ul style="list-style-type: none"> — for number pad — for Shift keys 	Keyboard with short-stroke keys English Stainless steel Black No 12 Yes; Free-standing Yes; Num, Caps and Scroll Yes Yes
Connection type	
<ul style="list-style-type: none"> • USB • PS/2 • Cable length 	Yes; Type A No 1.5 m; Typical
Frame size/design	
<ul style="list-style-type: none"> • Standard • Ergonomic 	Yes; For industrial applications Yes; 90° adjustable / tiltable
Ergonomics	
<ul style="list-style-type: none"> • Trackball rest • Adjustable height 	No Yes; By adjusting inclination angle 0° to 90°
Installation type/mounting	
Mounting	Max. load bearing capacity of 2 kg
Mounting type	Suitable for PRO devices
Mounting position	Horizontal
maximum permissible angle of inclination without external ventilation	90°; Between 0° and 90° in steps of 15°
Supply voltage	
Type of supply voltage	via USB
Input current	
Current consumption (rated value)	100 mA
Degree and class of protection	
IP65 (all-round)	Yes

Splashproof	Yes
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C
• Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	45 °C
• Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
• Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
Ambient temperature during storage/transportation	
• min.	0 °C
• max.	50 °C
Relative humidity	
• Operation, max.	80 %; no condensation
• Condensation permissible	No; Condensation not permissible
Operating systems	
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Windows 10	Yes
Mechanics/material	
Material	
• Aluminum	Yes; Powder-coated, RAL 9006
• Stainless steel	Yes; Keyboard itself
Service life	
• Number of operating cycles, keys	10 000 000; Operations (minimum)
Dimensions	
Width	481 mm
Height	20 mm
Depth	171.6 mm
Weights	
Weight without packaging	3 700 g
Weight incl. packaging	5 300 g
Scope of supply	
Delivery quantity in pieces	1; With support arm bracket
Components included	a basic adapter is required for mounting, this must be ordered separately
Other	
Merchandise	Yes
Manufacturer name	Sasse Elektronik GmbH
Manufacturer's address	Berliner Straße 12, 91126 Schwabach, Germany
Target devices	Merchandise suitable for 16:9 PRO devices
Note:	Successor 6AV688-10AU14-1DB0

last modified:

6/2/2020 