

USB keyboard INT for 4:3 PRO devices, in stainless steel, RAL9023 (gray), with numerical keypad, inclination adjustable Further information, Quantity and content: see technical data



General information	
Product type designation	USB-INOX keyboard PRO, mouse keys
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> <li>• Design</li> <li>• Keyboard assignment</li> <li>• Color of the buttons</li> <li>• Color of the key inscription</li> <li>• Key illumination</li> <li>• Function keys                             <ul style="list-style-type: none"> <li>— Number of function keys</li> </ul> </li> <li>• Number pad</li> <li>• status LED displays                             <ul style="list-style-type: none"> <li>— for number pad</li> <li>— for Shift keys</li> </ul> </li> </ul>	Keyboard with short-stroke keys English Stainless steel Black No  12 Yes; Free-standing Yes; Num, Caps and Scroll Yes Yes
Connection type	
<ul style="list-style-type: none"> <li>• USB</li> <li>• PS/2</li> <li>• Cable length</li> </ul>	Yes; Type A No 1.5 m; Typical
Frame size/design	
<ul style="list-style-type: none"> <li>• Standard</li> <li>• Ergonomic</li> </ul>	Yes; For industrial applications Yes; 90° adjustable / tiltable
Ergonomics	
<ul style="list-style-type: none"> <li>• Trackball rest</li> <li>• Adjustable height</li> </ul>	No Yes; By adjusting inclination angle 0° to 90°
Installation type/mounting	
Mounting	Max. load bearing capacity of 2 kg
Mounting type	Suitable for PRO devices
Mounting position	Horizontal
maximum permissible angle of inclination without external ventilation	90°; Between 0° and 90° in steps of 15°
Supply voltage	
Type of supply voltage	via USB
Input current	
Current consumption (rated value)	100 mA; Typical
Degree and class of protection	
IP65 (all-round)	Yes

Splashproof	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
BIS	No
RoHS conformity	Yes
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C
• Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	45 °C
• Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
• Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, min.	45 °C
Ambient temperature during storage/transportation	
• min.	0 °C
• max.	50 °C
Relative humidity	
• Operation, max.	80 %; no condensation
• Condensation permissible	No; Condensation not permissible
<b>Operating systems</b>	
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Windows 10	Yes
<b>Mechanics/material</b>	
Material	
• Aluminum	Yes; Powder-coated, RAL 9023
• Stainless steel	Yes; Keyboard itself
Service life	
• Number of operating cycles, keys	10 000 000; Operations (minimum)
<b>Dimensions</b>	
Width	481 mm
Height	20 mm
Depth	171.6 mm
<b>Weights</b>	
Weight without packaging	3 600 g
Weight incl. packaging	5 300 g
<b>Scope of supply</b>	
Delivery quantity in pieces	1; With support arm bracket
<b>Other</b>	
Merchandise	Yes; Sasse no. 1580.9905879
Manufacturer name	Sasse Elektronik GmbH
Manufacturer's address	Berliner Straße 12, 91126 Schwabach, Germany
contacting the manufacturer	Phone +49 9122 978-0, e-mail: info@sasse-elektronik.de
Target devices	Merchandise suitable for 4:3 PRO devices
<b>last modified:</b>	3/5/2021 