

Data sheet for Motor Module

Article No. : 6SL3320-1TE33-8AA3



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
DC link voltage	DC 510 ... 720 V
Electronics power supply	DC 24 V -15 % / +20 %
Current demand, max.	0.90 A
Current consumption 400V AC	1.80 A
DC-link current	
Rated current I_N DC	
- Basic/Smart Line Module	456 A
- Active Line Module	411 A
Base-load current I_L DC	
- Basic/Smart Line Module	444 A
- Active Line Module	400 A
Base-load current I_H DC	
- Basic/Smart Line Module	405 A
- Active Line Module	365 A
Output current	
Rated value I_N	
Rated value I_N	380 A
Base-load current I_L ¹⁾	370 A
Base load current I_H ²⁾	340 A
For S6 duty (40%) I_{S6}	430 A
I_{max}	555 A
Type rating ³⁾	
Based on I_N	250 kW
Based on I_H	160 kW
Pulse frequency	
Rated pulse frequency ⁴⁾	
Rated pulse frequency ⁴⁾	2.00 kHz
Pulse frequency, max.	2.00 kHz
DC link capacitance	7,800 μ F
Output frequency for servo control	0 ... 550 Hz
Output frequency for V/f control	0 ... 550 Hz
Output frequency for vector control	0 ... 550 Hz

Ambient conditions	
Installation altitude (without derating)	2,000 m (6,561.68 ft)
Cooling ⁵⁾	External air cooling
Cooling air requirement	0.36 m ³ /s (12.710 ft ³ /s)
Ambient temperature	
During operation	0 ... 40 °C (32 ... 104 °F)

Connections	
Motor end	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm ²
DC link	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm ²
Braking module	
Version	M6 threaded bolt
PE1 connection	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm ²
PE2 connection	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm ²
Max. motor cable length ⁶⁾	
Shielded	300 m (984.25 ft)
Unshielded	450 m (1,476.38 ft)

Standards	
Compliance with standards	CE, cULus
Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1

Mechanical data	
Line side	
Width	326 mm (12.83 in)
Height	1,533 mm (60.35 in)
Depth	545 mm (21.46 in)
Degree of protection	IP20
Type of construction	Chassis
Net weight	136 kg (299.83 lb)

General tech. specifications	
Sound pressure level (1m) + 50 Hz / 60 Hz	69 dB / 73 dB
Power loss, max. ⁷⁾	
Power loss (50 Hz 400 V)	3.67 kW
Power loss (60 Hz 460 V)	3.80 kW

¹⁾The base load current I_L is based on a duty cycle of 110% for 60 s or 150% for 10 s with a duty cycle period of 300 s.

²⁾The base load current I_H is based on a duty cycle of 150% for 60 s or 160% for 10 s with a duty cycle duration of 300 s.

³⁾?PMD_ABX850_001_000 BEMESSUNGSLEISTUNG_EINES_TYP_6-POLIGEN_NORM-ASYNCHRONMOTORS_AUF_BASIS_IL_BZW_IH_BEI_3_AC_50_HZ_400_V_3_AC_60_HZ_460_V,?

⁴⁾Information on the correlation between pulse frequency and maximum output current/output frequency is provided in the SINAMICS Low Voltage Configuration Manual.

⁵⁾Power units with intensified air cooling thanks to integrated fan

⁶⁾?PMD_AAC559_001_000 SUMME_ALLER_MOTORLEITUNGEN_UND_ZWISCHENKREIS_HOEHERE_LEITUNGSLAENGEN_IN_ABHAENGIKHEIT_DER_PROJEKTIERUNG_AUF_ANFRAGE_WEITERE_HINWEISE_ENTHAELT_DAS_PROJEKTIERUNGSHANDBUCH_SINAMICS_LOW_VOLTAGE,?

⁷⁾The specified power loss represents the maximum value at 100% utilization. The value is lower under normal operating conditions.