

Touch pen, thin, for resistive touch screen Holding cord for Mobile Panel 277 10" and other resistive touch screens Further information, Quantity and content: see technical data

| General information | |
|---|--|
| Product type designation | Touch pen, thin, resistive technology |
| Control elements | |
| Frame size/design | |
| • Standard | Yes; For industrial applications |
| Installation type/mounting | |
| Wall mounting/direct mounting | Yes; using 40 cm retaining cord |
| Standards, approvals, certificates | |
| RoHS conformity | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | -40 °C |
| • max. | 80 °C |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 80 °C |
| Relative humidity | |
| • Operation, max. | 90 % |
| Mechanics/material | |
| Material | |
| • Plastic | Yes |
| Screw type | |
| • Torx | No |
| Dimensions | |
| Height | 125 mm; Length |
| Thickness | 8 mm; Diameter |
| Scope of supply | |
| Delivery quantity in pieces | 5; Incl. retaining cord for Mobile Panel 277 10" |
| Other | |
| Merchandise | No |
| Manufacturer's address | Gleiwitzerstraße 555, 90475 Nuremberg, Germany |
| Target devices | for resistive touch screens |
| Usable in the following products | |
| • Product 29 | 6AV2124-0UC02-0AX0 |

last modified:

1/15/2021 