

SITOP PSU8200/1ACDC/24VDC/20A

SITOP PSU8200 20 A Stabilized
power supply input: 120-230 V
AC 110-220 V DC output: 24 V
DC/20 A

Input	
Input	1-phase and 2-phase AC or DC
Rated voltage value V_{in} rated	120 ... 230 V
Voltage range AC	85 ... 275 V
<ul style="list-style-type: none"> Note 	Derating of temperature necessary down to 50 °C at $V_{in} < 100$ V AC or DC
supply voltage	
<ul style="list-style-type: none"> at DC 	110 ... 220 V
input voltage	
<ul style="list-style-type: none"> at DC 	88 ... 350 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 230$ V
Mains buffering at I_{out} rated, min.	20 ms; at $V_{in} = 230$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	45 ... 65 Hz
input current	
<ul style="list-style-type: none"> at rated input voltage 120 V 	4.6 A
<ul style="list-style-type: none"> at rated input voltage 230 V 	2.5 A
Switch-on current limiting (+25 °C), max.	20 A
I^2t , max.	5 A ² ·s
Built-in incoming fuse	Yes
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker at 1-phase operation: 10 A characteristic C; required at 2-phase operation: circuit breaker 2-pole connected or circuit breaker 3RV2711-1HD10 (UL 489) at 120 V or 3RV2711-1ED10 (UL 489) at 230 V
Output	
Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	24 V
<ul style="list-style-type: none"> output voltage at output 1 at DC rated value 	24 V
Total tolerance, static \pm	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.3 %
Residual ripple peak-peak, max.	100 mV
Residual ripple peak-peak, typ.	80 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	200 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	100 mV
Adjustment range	24 ... 28.8 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
Signaling	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
On/off behavior	No overshoot of V_{out} (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	50 ms
Rated current value I_{out} rated	20 A

Current range	0 ... 20 A
• Note	+60 ... +70 °C: Derating 3%/K
supplied active power typical	480 W
short-term overload current	
• at short-circuit during operation typical	60 A
duration of overloading capability for excess current	
• at short-circuit during operation	25 ms
constant overload current	
• on short-circuiting during the start-up typical	30 A
Parallel switching for enhanced performance	Yes; switchable characteristic
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at V_{out} rated, I_{out} rated, approx.	93 %
Power loss at V_{out} rated, I_{out} rated, approx.	42 W
Closed-loop control	
Dynamic mains compensation (V_{in} rated ± 15 %), max.	0.5 %
Dynamic load smoothing (I_{out} : 50/100/50 %), $U_{out} \pm$ typ.	1 %
Load step setting time 50 to 100%, typ.	1 ms
Load step setting time 100 to 50%, typ.	1 ms
setting time maximum	5 ms
Protection and monitoring	
Output overvoltage protection	< 33 V
Current limitation, typ.	21.5 A
property of the output short-circuit proof	Yes
Short-circuit protection	Alternatively, constant current characteristic approx. 23 A or latching shutdown
enduring short circuit current RMS value	
• typical	23 A
overcurrent overload capability in normal operation	overload capability 150 % I_{out} rated up to 5 s/min
Overload/short-circuit indicator	LED yellow for "overload", LED red for "latching shutdown"
Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	1 mA
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
Explosion protection	IECEx Ex nA nC IIC T3 Gc; ATEX (EX) II 3G Ex nA nC IIC T3 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T3
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
certificate of suitability EAC approval	Yes
Marine approval	ABS, DNV GL
EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
• during operation	-25 ... +70 °C
— Note	With natural convection; startup tested starting from -40 °C nominal

<ul style="list-style-type: none"> during transport during storage 	voltage -40 ... +85 °C -40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
Connection technology	screw-type terminals
Connections <ul style="list-style-type: none"> Supply input Output Auxiliary 	L, N, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.2 ... 4 mm ² 13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm ²
width of the enclosure	90 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing <ul style="list-style-type: none"> top bottom left right 	50 mm 50 mm 0 mm 0 mm
Weight, approx.	1.2 kg
product feature of the enclosure housing can be lined up	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Buffer module
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	667 048 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

