



Figure similar

Through-type terminals with screw terminal Terminal size 4.0 mm²
Terminal width 6.2 mm Color gray

Model	
product brand name	SENTRON
product designation	ALPHA FIX terminal blocks
design of terminal / terminal levels internally linked	No
General technical data	
terminal contact spacing	6.2 mm
operating voltage / rated value	1 000 V
Protection class	
combustibility class acc. to UL 94	V0
Main circuit	
operational current / rated value	30 A
Appearance	
color	grey
Product details	
product component / required / end cover plate	Yes
Number	
number of terminal levels	1
number of terminal points / per terminal level	2
Connections	
stripped length	9 mm
connectable conductor cross-section / solid	
• minimum	0.14 mm ²
• maximum	4 mm ²
connectable conductor cross-section / finely stranded	
• with core end processing / minimum	0.14 mm ²
• with core end processing / maximum	4 mm ²
tightening torque / with screw-type terminals	
• minimum	0.6 N·m
• maximum	0.8 N·m
type of electrical connection	
• 1	screw-type terminal
• 2	screw-type terminal
position / of the terminal	lateral
Mechanical Design	
height / with lowest-profile installation	47.5 mm
length	47.7 mm

fastening method	DIN rail 35 mm		
net weight	9 g		
material / of the insulating body	Thermoplast		
Environmental conditions			
ambient temperature / during operation			
• minimum	-25 °C		
• maximum	55 °C		
General Product Approval		Declaration of Conformity	other



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH1000-0AG00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WH1000-0AG00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH1000-0AG00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

