# **SIEMENS**

#### **Data sheet**

### 6GK1901-1BB10-2AE0

## product type designation

product description



#### IE FC RJ45 Plug 180 (2x2)

RJ45 data connector

Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC Cable 2x 2; 180 $^{\circ}$  cable outlet 1 pack = 50 units

suitability for use

For connection to IE FC TP cables 2x2, suitable for fast assembly with the FastConnect system

transfer rate

transfer rate / for Industrial Ethernet

10 Mbit/s. 100 Mbit/s

| transfer rate / for Industrial Ethernet                      | 10 Mbit/s, 100 Mbit/s   |
|--|---|
| interfaces   |   |
| number of electrical connections                             |   |
| <ul> <li>for Industrial Ethernet FC TP cables</li> </ul>     | 4   |
| for network components or terminal equipment                 | 1   |
| type of electrical connection                                |   |
| • for Industrial Ethernet FC TP cables                       | integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22 |
| for network components or terminal equipment                 | RJ45 connector  |
| type of electrical connection / FastConnect                  | Yes   |
| mechanical data  |   |
| material / of the enclosure                                  | metal   |
| number of reuses   | 10  |
| locking mechanism design                                     | other   |
| design, dimensions and weights                               |   |
| type of cable outlet   | 180° cable outlet   |
| width  | 13.7 mm   |
| height   | 16 mm   |
| depth  | 55 mm   |
| net weight   | 35 g  |
| connectable cable cross-section                              | 6.5 6.5 mm  |
| connectable conductor cross-section                          | 0.33 mm <sup>2</sup>  |
| ambient conditions   |   |
| ambient temperature  |   |
| during operation   | -40 +85 °C  |
| during storage   | -40 +85 °C  |
| during transport   | -40 +85 °C  |
| relative humidity  |   |
| at 25 °C / without condensation / during operation / maximum | 95 %  |
| protection class IP  | IP20  |
| product features, product functions, product components      | / general   |

product feature

| <ul> <li>PoE capability</li> </ul>  | Yes  |
|---|--|
| <ul><li>PoE+capability</li></ul>  | Yes  |
| • silicon-free  | Yes  |
| product component   |  |
| <ul><li>strain relief</li></ul>   | Yes  |
| standards, specifications, approvals                                      |  |
| certificate of suitability  |  |
| <ul> <li>RoHS conformity</li> </ul>                                       | Yes  |
| <ul> <li>UL approval</li> </ul>   | Yes  |
| <ul> <li>cULus approval</li> </ul>  | Yes  |
| <ul> <li>railway application in accordance with EN 50155</li> </ul>       | No   |
| standard for structured cabling   | Cat5                                       |
| further information / internet-Links                                      |  |
| Internet-Link   |  |
| <ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>         | http://www.siemens.com/tia-selection-tool  |
| <ul> <li>to website: Industrial communication</li> </ul>                  | http://www.siemens.com/simatic-net         |
| <ul><li>to website: Industry Mall</li></ul>                               | https://mall.industry.siemens.com          |
| <ul> <li>to website: Information and Download Center</li> </ul>           | http://www.siemens.com/industry/infocenter |
| <ul> <li>to website: Selection guide for cables and connectors</li> </ul> | https://sie.ag/2QdlxcP                     |
| <ul><li>to website: Image database</li></ul>                              | http://automation.siemens.com/bilddb       |
| <ul><li>to website: CAx-Download-Manager</li></ul>                        | http://www.siemens.com/cax                 |
| • to website: Industry Online Support                                     | https://support.industry.siemens.com       |