




Selector switch, illuminable, 22 mm, round, plastic, white, selector switch, short, 3 switch positions I-O-II, latching, actuating angle 2x45°, 10:30h/12h/13:30h

product brand name	SIRIUS ACT
product designation	Selector switches
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Plastic, black, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Selector, short
principle of operation of the actuating element	latching, 2x45° (10:30 h/12 h/13:30 h)
product extension optional	
• light source	Yes
• contact module	Yes
color of the actuating element	white
material of the actuating element	plastic
shape of the actuating element	Handle
outer diameter of the actuating element	32.3 mm
number of switching positions	3
actuating angle	
• clockwise	45°
• anticlockwise	45°
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	plastic
color of the front ring	black
General technical data	
protection class IP	IP66, IP67, IP69(IP69K)
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance	
• acc. to IEC 60068-2-27	sinusoidal half-wave 50g / 11 ms
• for railway applications acc. to DIN EN 61373	Category 1, Class B
vibration resistance	
• acc. to IEC 60068-2-6	10 ... 500 Hz: 5g
• for railway applications acc. to DIN EN 61373	Category 1, Class B
operating frequency maximum	1 800 1/h
mechanical service life (switching cycles) typical	1 000 000

reference code acc. to IEC 81346-2	S					
Substance Prohibition (Date)	01.10.2014 00:00:00					
Safety related data						
B10 value with high demand rate acc. to SN 31920	300 000					
proportion of dangerous failures						
• with low demand rate acc. to SN 31920	20 %					
• with high demand rate acc. to SN 31920	20 %					
failure rate [FIT] with low demand rate acc. to SN 31920	100 FIT					
T1 value for proof test interval or service life acc. to IEC 61508	20 y					
Ambient conditions						
ambient temperature						
• during operation	-25 ... +70 °C					
• during storage	-40 ... +80 °C					
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95 %)					
Installation/ mounting/ dimensions						
height	32.3 mm					
width	32.3 mm					
shape of the installation opening	round					
mounting diameter	22.3 mm					
positive tolerance of installation diameter	0.4 mm					
mounting height	28.8 mm					
installation width	32.3 mm					
installation depth	25.4 mm					
Certificates/ approvals						
General Product Approval	Declaration of Conformity	Test Certificates				
			Miscellaneous		Type Test Certificates/Test Report	
Test Certificates		Marine / Shipping				
Special Test Certificate						
other						
Confirmation						
Further information						
Information- and Downloadcenter (Catalogs, Brochures,...)						
https://www.siemens.com/ic10						
Industry Mall (Online ordering system)						
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1002-2BL60-0AA0						
Cax online generator						
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1002-2BL60-0AA0						
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)						
https://support.industry.siemens.com/cs/ww/en/ps/3SU1002-2BL60-0AA0						
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)						



last modified:

7/14/2021 