

SIMATIC IFP2200 Flat Panel 22" display (16: 9), Multitouch, Standard up to 5 m, 1920x 1080 pixels, for 24 V DC, display port/DVI interface incl. DVI/USB cable 1.8 m



Figure similar

General information	
Product type designation	IFP2200
Short designation	Flat Panel 22" multi-touch
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in; 22"
Screen diagonal [cm]	56 cm
Display width	476 mm
Display height	268 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	170° x 170°
Resolution (pixels)	
• Image resolution	1 920 x 1 080
• Horizontal image resolution	1 920 pixel
• Vertical image resolution	1 080 pixel
• Pixel size, horizontal	0.2475 mm
• Pixel size, vertical	0.2475 mm
General features	
• Brightness/contrast	250 cd/m² / 1 000:1
• non-reflective and tempered mineral glass screen	Yes
• Detachable from computer unit	5 m
• Luminance	250 cd/m²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	multi-touch screen
Input device	
• Integrated mouse cursor control	No
Keyboard fonts	
• Function keys	No
— Number of function keys	0
Touch operation	
• Design as touch screen	Yes; Projective-capacitive

• Monitor keyboard	Yes
<b>Installation type/mounting</b>	
Design	Built-in unit
Front mounting	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	35°
maximum permitted backward tilt angle from vertical	35°
<b>Supply voltage</b>	
Type of supply voltage	DC
Rated value (DC)	24 V; PELV
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
<b>Power loss</b>	
Power loss, typ.	40 W
Power loss, max.	65 W
<b>Interfaces</b>	
Video interfaces	
• analog video signal (VGA)	No
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	Yes
<b>Degree and class of protection</b>	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4 at the front	Yes
• Enclosure Type 4x at the front	Yes
• Enclosure Type 12 at the front	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes
Use in hazardous areas	
• ATEX Zone 2	Yes; Available soon
• ATEX Zone 22	Yes; Available soon
• FM Class I Division 2	Yes
Marine approval	
• Germanischer Lloyd (GL)	Yes; Available soon
• American Bureau of Shipping (ABS)	Yes; Available soon
• Bureau Veritas (BV)	Yes; Available soon
• Det Norske Veritas (DNV)	Yes; Available soon
• Lloyds Register of Shipping (LRS)	Yes; Available soon
• Nippon Kaiji Kyokai (Class NK)	Yes; Available soon
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C; Vertical installation (horizontal)
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; no condensation
Vibrations	
• Vibration load in operation	10 m/s <sup>2</sup>
• Vibration load during transport/storage	10 m/s <sup>2</sup>

Shock testing	
• Shock load during operation	150 m/s <sup>2</sup>
• shock acceleration during storage/transport	150 m/s <sup>2</sup>
Mechanics/material	
Enclosure material (front)	
• Glass	Yes
Dimensions	
Width of the housing front	560 mm
Height of housing front	380 mm
Mounting cutout, width	542 mm; Tolerance: +1 mm
Mounting cutout, height	362 mm; Tolerance: +1 mm
Overall depth	62.5 mm
Weights	
Weight (without packaging)	6.5 kg
Weight (with packaging)	7.6 kg

**last modified:**

12/16/2020 