



Fuse terminal thermoplast Screw terminal on both sides 10 mm Sz. 1.5

Model	
product brand name	ALPHA
type of light source / as defect indicator	without
design of the fuse link	others
design of fuse holder	without
General technical data	
insulation material	thermoplastic
terminal contact spacing	10 mm
Supply voltage	
operating voltage / rated value	250 V
type of voltage / for supply of the defect indicator	others
Protection class	
combustibility class acc. to UL 94	Other
Main circuit	
operational current / rated value	6.3 A
Appearance	
color	miscellaneous
Product details	
product component / required / end cover plate	No
Number	
number of terminal levels	1
Connections	
connectable conductor cross-section / solid	
• minimum	1 mm ²
• maximum	1 mm ²
connectable conductor cross-section / stranded	
• maximum	1.5 mm ²
connectable conductor cross-section / finely stranded	
• with core end processing / minimum	0.75 mm ²
• with core end processing / maximum	1.5 mm ²
type of electrical connection	
• 1	screw-type terminal
• 2	screw-type terminal
position / of the terminal	lateral
Mechanical Design	
height / with lowest-profile installation	42 mm

length	57 mm		
fastening method	DIN rail 35 mm		
material / of the insulating body	Thermoplast		
General Product Approval		Declaration of Conformity	Test Certificates
			other



[Miscellaneous](#)

[Environmental Confirmations](#)

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1SF12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1SF12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

