


product description



PROFIBUS bus connector, RS 485, screw, without programming port, 35°
SIPLUS DP PB CONNECTOR W R - TILTED CABLE OUTLET -40 ... +70 °C with conformal coating based on 6ES7972-0BA41-0XA0

Figure similar

suitability for use	For connecting PROFIBUS stations to the PROFIBUS bus cable
transfer rate	
transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
type of electrical connection	
• for PROFIBUS cables	Screw
• for network components or terminal equipment	9-pin sub D connector
type of electrical connection / FastConnect	No
mechanical data	
design of terminating resistor	Resistor combination integrated and connectable via slide switch
material / of the enclosure	plastic
locking mechanism design	Screwed joint
design, dimensions and weights	
type of cable outlet	35 degree cable outlet
width	15.8 mm
height	54 mm
depth	39.5 mm
net weight	60 g
ambient conditions	
ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• in horizontal mounting position / during operation	70 ... -40 °C
• during storage and transport	70 ... -40 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
• with condensation / maximum	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)
• with condensation / acc. to IEC 60068-2-38 /	100 %; RH including condensation/frost (no commissioning when

maximum	condensation is present), horizontal installation
resistance to biologically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 • conformity acc. to EN 60721-3-6 	<p>Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request</p> <p>Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request</p>
resistance to chemically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 • conformity acc. to EN 60721-3-6 	<p>Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p>
resistance to mechanically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 • conformity acc. to EN 60721-3-6 	<p>Yes; Class 3S4 incl. sand, dust, *</p> <p>Yes; Class 6S3 incl. sand, dust; *</p>
environmental category / acc. to IEC 60721 / note	* The supplied plug covers must remain in place over the unused interfaces during operation!
coating / for equipped printed circuit board / acc. to EN 61086	Yes; Class 2 for high reliability
type of coating <ul style="list-style-type: none"> • protection against pollution according to EN 60664-3 • for electronic devices in railway applications acc. to EN 50155 	<p>Yes; Type 1 protection</p> <p>Yes; protective coating of the Class PC2 according to EN 50155:2022</p>
type of test / of the coating / acc. to MIL-I-46058C	Yes; Discoloration of coating possible during service life
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal coating, Class A
protection class IP	IP20
product features, product functions, product components / general	
product feature <ul style="list-style-type: none"> • silicon-free 	Yes
product component <ul style="list-style-type: none"> • PG connection socket • strain relief 	<p>No</p> <p>Yes</p>
standards, specifications, approvals	
certificate of suitability <ul style="list-style-type: none"> • RoHS conformity • UL approval 	<p>Yes</p> <p>Yes</p>
reference code <ul style="list-style-type: none"> • acc. to IEC 81346-2 	XG
further information / internet-Links	
Internet-Link <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Selection guide for cables and connectors • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	<p>http://www.siemens.com/snst</p> <p>http://www.siemens.com/simatic-net</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>https://sie.ag/2QdlxcP</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>

last modified:

7/9/2021 