

PE terminal 2 screw terminals green-yellow, 6mm, Sz. 2.5



Figure similar

Model	
product brand name	ALPHA
General technical data	
insulation material	thermoplastic
terminal contact spacing	6 mm
Protection class	
combustibility class acc. to UL 94	V2
Appearance	
color	green-yellow
Product details	
product feature / PEN function	No
product component / required / end cover plate	No
Number	
number of terminal levels	2
number of terminal points / per terminal level	1
Connections	
stripped length	11 mm
connectable conductor cross-section / solid	
• maximum	2.5 mm²
connectable conductor cross-section / stranded	
• maximum	2.5 mm²
connectable conductor cross-section / finely stranded	
• with core end processing / maximum	2.5 mm²
• without core end processing / maximum	2.5 mm²
tightening torque / with screw-type terminals	
• minimum	0.5 N·m
• maximum	0.5 N·m
type of electrical connection	
• 1	screw-type terminal
• 2	screw-type terminal
position / of the terminal	lateral
Mechanical Design	
height / with lowest-profile installation	26 mm
length	51 mm
fastening method	DIN rail 35 mm
net weight	20 g

material / of the insulating body	Thermoplastic		
Environmental conditions			
ambient temperature / during operation			
• minimum	-25 °C		
• maximum	55 °C		
General Product Approval	Declaration of Conformity	Test Certificates	other



[Miscellaneous](#)

[Miscellaneous](#)

other

[Environmental Conformations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1PF00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1PF00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1PF00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

