

Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A. Rating: 1200A Wattage: 3W No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material: 304SS Enclosure: TYPE 12. 2-3 point mounting holes. Insulation: YES O. Cycles: 2500 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDUSTRIAL

| | |
|----------------------------------------------------|-----------------------------|
| principle of operation of the actuating element | SINGLE THROW |
| mechanical service life (switching cycles) typical | 2500 |
| fastening method | 2 OR 3 POINT MOUNTING HOLES |
| number of poles | 3 |
| Electricity | |
| ampacity | 1200 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| voltage between phase and Ground (GND) rated value | 600 V |
| Switching capacity | |
| switching capacity active power | 3 W |
| Model | |
| product brand name | SIEMENS |
| product type designation | ENCLOSED/SAFETY SWITCH |
| Mechanical Design | |
| design of the housing | TYPE 3R/ 3S/ 12/ 13 |
| material | Galv. Steel, Painted |
| General product approval | |
| certificate of suitability | UL |

last modified:

1/6/2021 