



Cable connector size S00 Spring-type terminal

General technical data		
product brand name		SIRIUS
product designation		Connection plug
design of the product		Size S00
size of the circuit-breaker		S00
protection class IP on the front acc. to IEC 60529		IP20
touch protection on the front acc. to IEC 60529		finger-safe, for vertical contact from the front
ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	-20 ... +60
ampacity maximum	A	16
Installation/ mounting/ dimensions		
width	mm	44.8
height	mm	40.2
depth	mm	79.6
Certificates/ approvals		
certificate of suitability		CE / UL / CSA / CCC
General Product Approval	Test Certificates	Shipping Approval



[Special Test Certificate](#)



LRS

Shipping Approval	other	Railway
	Confirmation	Vibration and Shock

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RV2917-5AA00 Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2917-5AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2917-5AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2917-5AA00&lang=en



last modified:

12/15/2020 