



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 600V A. Rating: 200A No. Of Poles: 3P F. Rating: 60Hz Action: SINGLE THROW Material: SS Enclosure: TYPE 4X. 2-3 point mounting holes. Insulation: YES O. Cycles: 8000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: INDUSTRIAL CORROSIVE RESISTANCE

installation location	INDUSTRIAL CORROSIVE RESISTANCE
principle of operation of the actuating element	SINGLE THROW
mechanical service life (operating cycles) typical	8000
fastening method	2 OR 3 POINT MOUNTING HOLES
number of poles	3
<b>Electricity</b>	
ampacity	200 A
supply voltage frequency rated value 50/60 Hz	Yes
voltage between phase and phase rated value	600 V
<b>Environmental conditions</b>	
ambient temperature during operation maximum	120 °C
ambient temperature during operation minimum	-20 °C
<b>Model</b>	
product brand name	SIEMENS
product type designation	ENCLOSED/SAFETY SWITCH
<b>Mechanical Design</b>	
design of the housing	TYPE 4X
material	SS
<b>General product approval</b>	
certificate of suitability	UL

last modified:

1/6/2021 