

product type designation



Lightning protector LP798-2N

Lightning protector LP798-2N, Lightning protection element with N/N Female/female connection, IP65 (-40...+85 °C), 2 ... 6 GHz, with Quarter-Wave technology for SCALANCE W antennas, compact instructions as hard copy German/English

suitability for operation

Quarter-wave short-circuited type; preferably used in IWLAN

interfaces

number of electrical connections	2
type of electrical connection	N-Connector
design of plug-in connection	female / female

electrical data

transmission frequency	2000 ... 6000 MHz
insertion loss	= 0.2 dB
impedance	50 Ω

ambient conditions

ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
suitability for use	
• for interior use	Yes
• for outside use	Yes
protection class IP	IP68

design, dimensions and weights

width	89.6 mm
diameter	29 mm
net weight	80 g

product features, product functions, product components / general

product feature / silicon-free	Yes
--------------------------------	-----

further information / internet-Links

Internet-Link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>
<http://www.siemens.com/simatic-net>
<https://www.siemens.com/industrymall>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

1/21/2021 