



busbar adapter 60 mm SYS UL 508 Busbar system 60 mm Bar thickness:
5/10 mm/TT profile UL rating 100A/600V Can be used in spring circuits IEC
rating 100 A/690 V for SIRIUS circuit breaker for SIRIUS Size S3 for cable
outlet top Cable welded 150° 153mm Adapter length 200 mm Adapter
width 72 mm

Model	
product brand name	SETRON
product designation	Device adapter
design of the product	Accessories
operational current / at AC / rated value	100 A
Mechanical Design	
height	200 mm
width / of the adapter	72 mm
depth	55 mm
thickness / of the busbar	
• minimum	5 mm
busbar center-to-center spacing	60 mm
net weight	650 g
General Product Approval	



Declaration of Conformity	Test Certificates				Marine / Shipping
 EG-Konf.	UK Declaration of Conformity	Special Test Certifi- cate	Miscellaneous	Type Test Certifi- cates/Test Report	 ABS

Marine / Shipping					
	 LRS	 PRS	 RINA	 RMRS	 DNV GL

other

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1211-4TR00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1211-4TR00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1211-4TR00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



