

SCALANCE XR552-12M; managed IE switch; 19" rack; 4x 1000/10000 Mbit/s SFP+; 12x 100/1000 Mbit/s 4-port media modules, electrical, electrical PoE or optical; LED diagnostics; error signaling contact; Select/set pushbutton, PROFINET IO device, network management, integrated redundancy manager; office features (RSTP, VLAN, IGMP, ...); C-plug in scope of delivery Layer 3 prepared; ports in the front



| | |
|--|--|
| product type designation | SCALANCE XR552-12M |
| transfer rate | |
| transfer rate | 10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10 Gbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| <ul style="list-style-type: none"> for network components or terminal equipment for Power-over-Ethernet / for network components or terminal equipment | RJ45 12 |
| number of electrical connections | |
| <ul style="list-style-type: none"> for SFP+ | 4 |
| interfaces / for communication / plug-in | |
| number of 100 Mbit/s ST(BFOC) ports | |
| <ul style="list-style-type: none"> for multimode for single mode (LD) | 48 48 |
| number of 1000 Mbit/s SC ports | |
| <ul style="list-style-type: none"> for multimode for single mode (LD) | 48 48 |
| number of electrical connections | |
| <ul style="list-style-type: none"> for SFP for SFP+ | 4 4 |
| interfaces / other | |
| number of electrical connections | |
| <ul style="list-style-type: none"> for operator console for management purposes for signaling contact for media module for power supply | 1 1 1 12 1 |
| type of electrical connection | |
| <ul style="list-style-type: none"> for operator console for management purposes for signaling contact for power supply | RJ11 RJ45 2-pole terminal block 4-pole terminal block |
| design of the removable storage | |
| <ul style="list-style-type: none"> C-PLUG/KEY-PLUG | Yes |
| product feature / hot-swappable interface modules | Yes |
| signal inputs/outputs | |
| operating voltage / of the signaling contacts | |

| | |
|--|---|
| <ul style="list-style-type: none"> • at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| <ul style="list-style-type: none"> • at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| type of voltage supply / redundant power supply unit | No |
| supplied active power / of PSE / with PoE | |
| <ul style="list-style-type: none"> • per port / maximum | 30 W |
| <ul style="list-style-type: none"> • total / maximum | 180 W |
| type of voltage / 1 / of the supply voltage | DC |
| <ul style="list-style-type: none"> • supply voltage / 1 / rated value | 24 V |
| <ul style="list-style-type: none"> • power loss [W] / 1 / rated value | 34.08 W |
| <ul style="list-style-type: none"> • supply voltage / 1 / rated value | 19.2 ... 28.8 V |
| <ul style="list-style-type: none"> • consumed current / 1 / maximum | 12.5 A |
| <ul style="list-style-type: none"> • type of electrical connection / 1 / for power supply | 4-pole terminal block |
| <ul style="list-style-type: none"> • product component / 1 / fusing at power supply input | Yes |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> • during operation | 0 ... 60 °C |
| <ul style="list-style-type: none"> • during storage | -40 ... +70 °C |
| <ul style="list-style-type: none"> • during transport | -40 ... +70 °C |
| <ul style="list-style-type: none"> • note | Operation with integral fan, replaceable |
| relative humidity | |
| <ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | 19" rack |
| number of modular height units / relating to 19-inch cabinet | 3 |
| width | 449 mm |
| height | 130.8 mm |
| depth | 305 mm |
| net weight | 10 kg |
| fastening method | |
| <ul style="list-style-type: none"> • 19-inch installation | Yes |
| <ul style="list-style-type: none"> • 35 mm top hat DIN rail mounting | No |
| <ul style="list-style-type: none"> • wall mounting | No |
| <ul style="list-style-type: none"> • S7-300 rail mounting | No |
| <ul style="list-style-type: none"> • S7-1500 rail mounting | No |
| type of cable outlet | Cable outlet at front |
| product features, product functions, product components / general | |
| cascading in cases of star topology | any (depending only on signal propagation time) |
| product functions / management, configuration, engineering | |
| product function | |
| <ul style="list-style-type: none"> • CLI | Yes |
| <ul style="list-style-type: none"> • web-based management | Yes |
| <ul style="list-style-type: none"> • MIB support | Yes |
| <ul style="list-style-type: none"> • TRAPs via email | Yes |
| <ul style="list-style-type: none"> • configuration with STEP 7 | Yes |
| <ul style="list-style-type: none"> • RMON | Yes |
| <ul style="list-style-type: none"> • port mirroring | Yes |
| <ul style="list-style-type: none"> • multiport mirroring | Yes |
| <ul style="list-style-type: none"> • CoS | Yes |
| <ul style="list-style-type: none"> • PROFINET IO diagnosis | Yes |
| PROFINET conformity class | B |
| product function / switch-managed | Yes |
| telegram length / for Ethernet / maximum | 9216 byte |
| protocol / is supported | |

| | |
|--|--|
| • Telnet | Yes |
| • HTTP | Yes |
| • HTTPS | Yes |
| • TFTP | Yes |
| • FTP | Yes |
| • BOOTP | Yes |
| • GMRP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| • SNMP v1 | Yes |
| • SNMP v2 | Yes |
| • SNMP v3 | Yes |
| • IGMP (snooping/querier) | Yes |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 – higher level designation/location designation | Yes |
| product functions / diagnostics | |
| product function | |
| • port diagnostics | Yes |
| • statistics Packet Size | Yes |
| • statistics packet type | Yes |
| • error statistics | Yes |
| • SysLog | Yes |
| product functions / VLAN | |
| product function | |
| • VLAN - port based | Yes |
| • VLAN - protocol-based | Yes |
| • VLAN - IP-based | Yes |
| • VLAN dynamic | Yes |
| number of VLANs / maximum | 255 |
| number of VLANs - dynamic / maximum | 255 |
| protocol / is supported / GVRP | Yes |
| product functions / DHCP | |
| product function | |
| • DHCP client | Yes |
| • DHCP Option 82 | Yes |
| • DHCP Option 66 | Yes |
| • DHCP Option 67 | Yes |
| product functions / routing | |
| service / routing / note | IP routing in combination with KEY-PLUG XR-500 |
| product function | |
| • static IP routing | Yes |
| • static IP routing IPv6 | Yes |
| • dynamic IP routing | Yes |
| • dynamic IP routing IPv6 | Yes |
| protocol / is supported | |
| • RIPv2 | Yes |
| • RIPv6 for IPv6 | Yes |
| • OSPFv2 | Yes |
| • OSPFv3 for IPv6 | Yes |
| • VRRP | Yes |
| • VRRP for IPv6 | Yes |
| product functions / redundancy | |
| product function | |
| • ring redundancy | Yes |
| • High Speed Redundancy Protocol (HRP) | Yes |
| • high speed redundancy protocol (HRP) with redundancy manager | Yes |

| | |
|---|---|
| <ul style="list-style-type: none"> high speed redundancy protocol (HRP) with standby redundancy | Yes |
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product function | |
| <ul style="list-style-type: none"> media redundancy protocol (MRP) with redundancy manager | Yes |
| <ul style="list-style-type: none"> Media Redundancy Protocol Interconnection (MRP-I) | Yes |
| <ul style="list-style-type: none"> redundancy procedure STP | Yes |
| <ul style="list-style-type: none"> redundancy procedure RSTP | Yes |
| <ul style="list-style-type: none"> redundancy procedure RSTP+ | Yes |
| <ul style="list-style-type: none"> redundancy procedure MSTP | Yes |
| <ul style="list-style-type: none"> Parallel Redundancy Protocol (PRP)/operation in the PRP-network | Yes |
| <ul style="list-style-type: none"> Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |
| <ul style="list-style-type: none"> passive listening | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> LACP | Yes |
| product functions / security | |
| product function | |
| <ul style="list-style-type: none"> ACL - MAC-based | Yes |
| <ul style="list-style-type: none"> ACL - port/MAC-based | Yes |
| <ul style="list-style-type: none"> IEEE 802.1x (radius) | Yes |
| <ul style="list-style-type: none"> broadcast/multicast/unicast limiter | Yes |
| <ul style="list-style-type: none"> broadcast blocking | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> SSH | Yes |
| product functions / time | |
| product function | |
| <ul style="list-style-type: none"> SICLOCK support | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> NTP | Yes |
| <ul style="list-style-type: none"> SNTP | Yes |
| type of time synchronization | IEEE 1588 |
| standards, specifications, approvals | |
| standard | |
| <ul style="list-style-type: none"> for FM | FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 |
| <ul style="list-style-type: none"> for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1-03 |
| <ul style="list-style-type: none"> for emitted interference | EN 61000-6-4 (Class A) |
| <ul style="list-style-type: none"> for interference immunity | EN 61000-6-2 |
| standards, specifications, approvals / CE | |
| certificate of suitability / CE marking | Yes |
| standards, specifications, approvals / hazardous environments | |
| standard / for hazardous zone | EN 60079-0: 2009, EN60079-15: 2010, II 3 G Ex nA IIC T4 Gc, KEMA 07 ATEX 0145 X |
| <ul style="list-style-type: none"> from CSA and UL | ISA 12.12.01-2012 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4 |
| certificate of suitability | |
| <ul style="list-style-type: none"> CCC / for hazardous zone according to GB standard | Yes |
| standards, specifications, approvals / other | |
| certificate of suitability | EN 61000-6-2, EN 61000-6-4 |
| <ul style="list-style-type: none"> C-Tick | Yes |
| <ul style="list-style-type: none"> KC approval | Yes |
| <ul style="list-style-type: none"> E1 approval | No |
| <ul style="list-style-type: none"> E1 approval | No |
| further information / internet-Links | |

| | |
|---|--|
| <p>Internet-Link</p> <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support | <p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/simatic-net</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p> |
|---|--|

security information

| | |
|-----------------------------|--|
| <p>security information</p> | <p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)</p> |
|-----------------------------|--|

last modified:

7/1/2021 