



Figure similar

MLFB-Ordering data

6SL3040-0JA01-0AA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Inputs / outputs

Digital inputs

Number	5
Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	6 mA
Delay time L→H, typ. ¹⁾	15 µs
Delay time H→L, typ. ¹⁾	55 µs

Fail-safe digital inputs

Number ²⁾	3
----------------------	---

Analog inputs

Number	1
Voltage	-10 ... +10 V
Resolution	12 bit + sign
Internal resistor	15 kOhm

Digital I/O

Number ³⁾	4
----------------------	---

As input

Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	6 mA
Delay time L→H ¹⁾	5 µs
Delay time H→L ¹⁾	5 µs

As output

Continuous short-circuit proof	Yes
Voltage	DC 24 V
Load current per digital output, max.	100 mA
Delay time, approx.	150 µs

As fail-safe digital output

Number	1
--------	---

1) The specified delay times refer to the hardware. The actual reaction time depends on the time slot in which the digital input or output is processed.

2) 3 parameterizable, fail-safe digital inputs (floating), or alternatively 6 parameterizable digital inputs (floating)

3) can be parameterized - as DI - as DO



Figure similar

MLFB-Ordering data

6SL3040-0JA01-0AA0

Electrical data	
Power supply voltage	DC 24 V -15 % +20 %
Max. power consumption ⁴⁾	0.8 A
Power loss, max.	20 W
Protection, max.	20 A
On-board encoder interface	
Encoder evaluation	optional incremental encoder TTL/HTL or encoder SSI without incremental signals
Current consumption at 24 V DC	0.35 A
Current consumption at 5 V DC	0.35 A
Encoder frequency, max.	500 kHz
SSI baudrate	100 ... 250 kBaud The baud rate depends on cable length
SSI absolute position resolution	30 bit
Line length, max.	
TTL encoder ⁵⁾	100 m (328.08 ft)
HTL encoder unipolar signal	100 m (328.08 ft)
HTL encoder bipolar signal	300 m (984.25 ft)
SSI encoder	100 m (328.08 ft)
Mechanical data	
Dimensions	
Width	73 mm (2.87 in)
Height	195 mm (7.68 in)
Depth	71 mm (2.80 in)
Net weight	0.95 kg (2.09 lb)

Environmental conditions	
Installation altitude	1000 m (3280.84 ft)
Ambient temperature during	
Operation	0 ... 55 °C (32 ... 131 °F)
Storage	-25 ... 70 °C (-13 ... 158 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Relative humidity during	
Transport, max.	95 % at 40 °C (104 °F)
Connections	
PE connection	M5 screw
Supply voltage, max.	2.5 mm² (AWG14)
Digital inputs, max.	1.5 mm² (AWG16)
Digital inputs/outputs, max.	1.5 mm² (AWG16)
Communication	
Communication	PROFINET
Standards	
Compliance with standards	cULus

4) Power requirement 0.8 A for CU305 incl. 350 mA for HTL encoder + 0.5 A for PM340

5) TTL only bipolar signals; for bipolar signals, the signal lines must be twisted in pairs and shielded