## **SIEMENS**

Data sheet 3SB2404-0C



Contact block, 1 NC, flat connector terminal

product brand name	SIRIUS	
product designation	contact block	
product type designation	3SB2	
Contact block/ lampholder		
number of lampholders	0	
General technical data		
product function positive opening	Yes	
suitability for integration	pushbutton / selector button	
type of voltage		
of the operating voltage	AC/DC	
protection class IP		
<ul> <li>of the enclosure</li> </ul>	IP40	
of the terminal	IP00	
vibration resistance acc. to IEC 60068-2-6	20 200 Hz: 5g	
reference code acc. to IEC 81346-2	S	
Substance Prohibitance (Date)	01.07.2006 00:00:00	
operating voltage		
• at AC		
— at 50 Hz rated value	5 230 V	
— at 60 Hz rated value	5 230 V	
<ul> <li>at DC rated value</li> </ul>	5 230 V	
Auxiliary circuit		
number of NC contacts for auxiliary contacts	1	
number of NO contacts for auxiliary contacts	0	
number of CO contacts for auxiliary contacts	0	
operational current at AC-12		
<ul><li>at 24 V rated value</li></ul>	10 A	
<ul> <li>at 60 V rated value</li> </ul>	10 A	
<ul><li>at 110 V rated value</li></ul>	10 A	
at 230 V rated value	10 A	
operational current at AC-15		
at 24 V rated value	4 A	
• at 110 V rated value	4 A	
at 230 V rated value	4 A	
operational current at DC-12		
<ul><li>at 24 V rated value</li></ul>	6 A	
at 60 V rated value	5 A	

<ul> <li>at 110 V rated value</li> </ul>	2.5 A	
<ul> <li>at 230 V rated value</li> </ul>	1 A	
operational current at DC-13		
<ul> <li>at 24 V rated value</li> </ul>	3 A	
<ul> <li>at 60 V rated value</li> </ul>	1.2 A	
<ul> <li>at 110 V rated value</li> </ul>	0.7 A	
<ul> <li>at 230 V rated value</li> </ul>	0.3 A	
Connections/ Terminals		
type of electrical connection	tab terminals	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-25 +70 °C	
<ul> <li>during storage</li> </ul>	-40 +80 °C	
Installation/ mounting/ dimensions		
fastening method	clip-on	
height	19 mm	
width	8 mm	
depth	31 mm	
Certificates/ approvals		
General Product Approval		Declaration of Conformity

**®** 





<u>KC</u>

EAC



Declaration of Conformity

other

Miscellaneous Confirmation

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2404-0C


Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2404-0C

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SB2404-0C

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SB2404-0C&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SB2404-0C&lang=en</a>



last modified: 12/21/2020 🖸