

product type designation

Split Connect M12 Jack

PROFIBUS PA SplitConnect M12 jack, Connection element for direct connection of PB PA field devices with M12 interface to PB FC 1 pack=5 units



transfer rate	
transfer rate	
<ul style="list-style-type: none"> with PROFIBUS PA 	31.25 kbit/s
interfaces	
number of electrical connections	
<ul style="list-style-type: none"> for PROFIBUS cables 	1
type of electrical connection	
<ul style="list-style-type: none"> for PROFIBUS cables 	integrated insulation displacement contacts
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	-40 ... +85 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> during transport 	-40 ... +85 °C
protection class IP	IP67
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> silicon-free 	Yes
further information / internet-Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAX-Download-Manager to website: Industry Online Support 	http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	6/30/2021 