



SIMATIC DP, CM PROFIBUS DP for ET 200SP CPU module with PROFIBUS DP interface (9-pole D-sub socket) DP master for 125 DP slaves DP slave,

General information	
Product type designation	CM PROFIBUS DP
HW functional status	FS04
Engineering with	
STEP 7 TIA Portal configurable/integrated from version	V13 Update 3
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
1. Interface	
Interface types	
RS 485	Yes
Protocols	
PROFIBUS DP master	Yes
PROFIBUS DP slave	Yes
SIMATIC communication	Yes
PROFIBUS DP master	
Number of DP slaves, max.	125
Services	
PG/OP communication	Yes
Equidistance	No
Isochronous mode	No
Activation/deactivation of DP slaves	Yes
PROFIBUS DP slave	
Transmission rate, max.	12 Mbit/s
automatic baud rate search	Yes
Address area, max.	120
User data per address area, max.	128 byte
Services	
PG/OP communication	Yes; Only with active interface
Routing	Yes; Only with active interface
S7 communication	Yes; Only with active interface
Direct data exchange (slave-to-slave communication)	Yes; No subscriber possible - only passive publisher
DPV1	Yes
Transfer memory	

— Inputs	244 byte
— Outputs	244 byte
Interface types	
RS 485	
• Transmission rate, max.	12 Mbit/s
• Cable length, max.	100 m
Protocols	
SIMATIC communication	
• S7 routing	Yes
• Data record routing	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnostics indication LED	
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	
between backplane bus and interface	Yes
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-25 °C; No condensation
• horizontal installation, max.	60 °C
• vertical installation, min.	-25 °C; No condensation
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	35 mm
Height	117 mm
Depth	75 mm
Weights	
Weight, approx.	80 g
last modified:	12/16/2020 