



Lampholder, Wedge base W2 x 4.6 d, without lamp, with holder

|                                                     |                     |
|-----------------------------------------------------|---------------------|
| <b>product brand name</b>                           | SIRIUS              |
| <b>product designation</b>                          | lampholder          |
| <b>product type designation</b>                     | 3SB2                |
| <b>Contact block/ lampholder</b>                    |                     |
| <b>socket design</b>                                | W2 x 4.6d           |
| <b>number of lampholders</b>                        | 1                   |
| <b>General technical data</b>                       |                     |
| <b>product function EMERGENCY STOP function</b>     | No                  |
| <b>product component</b>                            |                     |
| • diode                                             | No                  |
| • lamp transformer                                  | No                  |
| • light source                                      | No                  |
| • series resistor                                   | No                  |
| <b>suitability for integration</b>                  | front element       |
| <b>protection class IP</b>                          |                     |
| • of the enclosure                                  | IP00                |
| • of the terminal                                   | IP00                |
| <b>vibration resistance acc. to IEC 60068-2-6</b>   | 20 ... 200 Hz: 5g   |
| <b>reference code acc. to IEC 81346-2</b>           | P                   |
| <b>Substance Prohibitance (Date)</b>                | 01.07.2006 00:00:00 |
| <b>operating voltage</b>                            |                     |
| • at AC                                             |                     |
| — at 50 Hz rated value                              | 5 ... 60 V          |
| — at 60 Hz rated value                              | 5 ... 60 V          |
| • at DC rated value                                 | 5 ... 60 V          |
| <b>Auxiliary circuit</b>                            |                     |
| <b>number of NC contacts for auxiliary contacts</b> | 0                   |
| <b>number of NO contacts for auxiliary contacts</b> | 0                   |
| <b>number of CO contacts for auxiliary contacts</b> | 0                   |
| <b>operational current at DC-13</b>                 |                     |
| • at 24 V rated value                               | 3 A                 |
| <b>Connections/ Terminals</b>                       |                     |
| <b>type of electrical connection</b>                | tab terminals       |
| <b>Ambient conditions</b>                           |                     |
| <b>ambient temperature</b>                          |                     |
| • during operation                                  | -25 ... +60 °C      |
| • during storage                                    | -40 ... +80 °C      |

| Installation/ mounting/ dimensions |                      |
|------------------------------------|----------------------|
| fastening method                   | front panel mounting |
| height                             | 19 mm                |
| width                              | 19 mm                |
| depth                              | 46 mm                |

| Certificates/ approvals  |                           |
|--------------------------|---------------------------|
| General Product Approval | Declaration of Conformity |



|                           |       |
|---------------------------|-------|
| Declaration of Conformity | other |
|---------------------------|-------|

[Miscellaneous](#)

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2304-2A>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2304-2A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB2304-2A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB2304-2A&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2304-2A&lang=en)

last modified:

12/21/2020