



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Duplex, Triplex, Quadplex are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: MH-T, Quadplex Special Features: Features: 1/2 IN width-per-pole construction; Wire Size: 14-6 AWG Copper, 12-6 AWG Aluminum Std: UL Listed, CSA Certified, SWD, HACR Rated V. Rating: 120/240 A. Rating: (1) 2-Pole: 20 AMP, (1) 2-Pole: 30 AMP Interrupt Rating: 10 Number Of Poles: 4 Length: 3/1/2008 Width: 2 Height: 3 Operating Temperature: 40

|                                              |                                                                                             |
|----------------------------------------------|---------------------------------------------------------------------------------------------|
| number of poles                              | 4                                                                                           |
| Environmental conditions                     |                                                                                             |
| ambient temperature during operation maximum | 40 °C                                                                                       |
| Model                                        |                                                                                             |
| product brand name                           | SIEMENS                                                                                     |
| special product feature                      | Features: 1/2 IN width-per-pole construction; Wire Size: 14-6 AWG Copper, 12-6 AWG Aluminum |
| Mechanical Design                            |                                                                                             |
| design of the product                        | MH-T, Quadplex                                                                              |
| height [in]                                  | 3 in                                                                                        |
| width [in]                                   | 2 in                                                                                        |
| General product approval                     |                                                                                             |
| standard                                     | UL Listed, CSA Certified, SWD, HACR Rated                                                   |

last modified: 1/7/2021 