

product type designation



Split Connect Tap

PROFIBUS PA SplitConnect TAP; for setting up PROFIBUS PA segments and connection of PA field devices, insulation displacement method, IP67
Type of delivery: 10 units=1 pack

transfer rate	
transfer rate	
• with PROFIBUS PA	31.25 kbit/s
interfaces	
number of electrical connections	
• for PROFIBUS cables	3
type of electrical connection	
• for PROFIBUS cables	integrated insulation displacement contacts
mechanical data	
material / of the enclosure	PBT (polybutyleneterephthalate)
design, dimensions and weights	
width	84 mm
height	54 mm
depth	49 mm
net weight	170 g
fastening method	
• 35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
ambient conditions	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP67
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
• UL approval	Yes
further information / internet-Links	
Internet-Link	
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb

- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

6/30/2021 