SIEMENS

Data sheet

6ES7193-6BP20-0BB0



SIMATIC ET 200SP, BaseUnit BU20-P12+A4+0B, BU type B0, Push-in terminals, with 4 AUX terminals, bridged to the left, WxH: 20 mmx117 mm

General information	
Product type designation	BU type B0
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	See manual
 For P1 and P2 bus 	24 V
• For AUX bus	24 V; Equal potential group to P1/P2 bus or PE
for process terminals	24 V
Rated value (AC)	See manual
 For P1 and P2 bus 	230 V
• For AUX bus	230 V; Equal potential group to P1/P2 bus or PE
 for process terminals 	230 V
Mains filter	
integrated	No
Current carrying capacity	
up to 60 °C, max.	10 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	5 A
Hardware configuration	
Automatic encoding	Yes
Slots	
Number of slots	1
Potential separation	
between backplane bus and supply voltage	Yes
between process terminals and supply voltage	Yes
between power bus and supply voltage	No
Isolation	
Isolation tested with	3 100 V DC
Ambient conditions	
Ambient temperature during operation	
 horizontal installation, min. 	-30 °C
 horizontal installation, max. 	60 °C
 vertical installation, min. 	-30 °C
 vertical installation, max. 	50 °C
Altitude during operation relating to sea level	
 Installation altitude above sea level, max. 	2 000 m; On request: Installation altitudes greater than 2 000 m

Accessories	
Color coding labels	
 for AUX terminals 	CC81 to CC83
Connection method	
Terminals	
Terminal type	Push-in terminal
 Conductor cross-section, min. 	0.14 mm²; AWG 26
 Conductor cross-section, max. 	2.5 mm²; AWG 14
 Number of process terminals to I/O module 	12; Pro slot
 Number of terminals to AUX bus 	0
 Number of add-on terminals 	0
 Number of terminals with connection to P1 and P2 bus 	0; Pro slot
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	48 g
	_

last modified:

2/7/2021 🖸