



Device adapter MCCB, 3-pole, 250 A Busbar center-to-center spacing 60 mm for 3VA12/20/21/22/52/61/62 241 mm x 105 mm Contacting to the adapter is supplied as well

Model	
product brand name	SENTRON
product designation	Device adapter
design of the product	Accessories
operational current / at AC / rated value	250 A
Connections	
type of electrical connection	Tubular contacts
Mechanical Design	
height	240 mm
width / of the adapter	105 mm
depth	35 mm
thickness / of the busbar	
• minimum	5 mm
busbar center-to-center spacing	60 mm
net weight	1 231 g
General Product Approval	

[Confirmation](#)



Declaration of Conformity	Test Certificates	Marine / Shipping
---------------------------	-------------------	-------------------



EG-Konf.

[Miscellaneous](#)

[Special Test Certificate](#)



Marine / Shipping	other
-------------------	-------



[Miscellaneous](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AP03>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AP03>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AP03

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



