

product type designation

Power Supply PS598-1

SCALANCE PS598-1 Power-Supply 300 W input: 85-264 V AC IEC plug;
Output: DC 24 V connecting terminals or for direct connection to
SCALANCE X-500.



type of current supply

300 W, input: 85-264 V, output:DC 24

electrical data / input

voltage curve / at input	AC single phase
supply voltage / at AC	85 ... 264 V
supply voltage / 1 / at AC / rated value	230 V
design of input / wide range input	Yes
overvoltage category	Category II (20 A rated branch circuit)
buffering time / for rated value of the output current / in the event of power failure / minimum	16 ms
line frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
line frequency	47 ... 63 Hz
input current / at rated input voltage 230 V / rated value	1.8 A
current limitation / of inrush current / at 25 °C / maximum	40 A
fuse protection type / at input	replaceable

electrical data / output

voltage curve / at output	Controlled, isolated DC voltage
output voltage / at DC / rated value	24 V
display version / for normal operation	Green LED for 24 V ok and fault LED
behavior of the output voltage / when switching on	Overshoot of $U_a < 5\%$
startup delay time / maximum	1.5 s
voltage increase time / of the output voltage / maximum	15 ms
output current	
• rated value	12.5 A
• rated range	0 ... 12.5 A
supplied active power / typical	300 W
product feature / parallel switching of channels	Yes
number of parallel-switched equipment resources / for increasing the power	2
efficiency in percent	87 %
power loss [W]	39 W

electrical data / closed-loop control

relative overall tolerance / of the voltage	2 %
residual ripple / maximum	0.36 V
voltage peak / maximum	240 V
relative control precision / of the output voltage	
• on slow fluctuation of input voltage	0.2 %
• on slow fluctuation of ohm loading	0.4 %

<ul style="list-style-type: none"> load step of resistive load 50/100/50 % / typical with rapid fluctuation of the input voltage by +/- 15% / typical 	<p>3.25 %</p> <p>0.8 %</p>
setting time <ul style="list-style-type: none"> load step 50 to 100% / typical load step 100 to 50% / typical 	<p>2 ms</p> <p>2 ms</p>
electrical data / protection and monitoring	
design of the overvoltage protection / at output	< 37 V
response value current limitation / typical	1.15 A
property of the output / short-circuit proof	Yes
design of short-circuit protection	Electronic shutdown, automatic restart
electrical data / safety	
galvanic isolation / between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current <ul style="list-style-type: none"> maximum typical 	<p>3 mA</p> <p>0.858 mA</p>
interfaces	
type of electrical connection <ul style="list-style-type: none"> at input at output 	<p>IEC plug</p> <p>for plugging into basic device or screw terminal in accordance with specification</p>
design, dimensions and weights	
width	446 mm
height	44 mm
depth	140 mm
net weight	1.7 kg
product feature / of the enclosure / housing can be lined up	No
fastening method <ul style="list-style-type: none"> 19-inch installation wall mounting standard rail mounting S7-300 rail mounting 	<p>Plugged into the basic unit or rack mounted</p> <p>Yes</p> <p>No</p> <p>No</p> <p>No</p>
ambient conditions	
ambient temperature <ul style="list-style-type: none"> during operation during storage during transport note 	<p>60 °C</p> <p>-25 ... +70 °C</p> <p>-25 ... +70 °C</p> <p>Operation with integral fan, non-replaceable</p>
environmental category / according to IEC 60721	Climate class 3K3, without condensation
protection class IP	IP20
standards, specifications, approvals	
standard <ul style="list-style-type: none"> for safety / from CSA and UL for emitted interference for interference immunity 	<p>UL 60950-1, CSA C22.2 No. 60950-1</p> <p>EN 55022 (Class B)</p> <p>EN 61000-6-2</p>
certificate of suitability <ul style="list-style-type: none"> CE marking C-Tick E1 approval E1 approval railway application in accordance with EN 50155 railway application in accordance with EN 50124-1 IEC 61850-3 	<p>EN 55022, EN 61000-6-4</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
MTBF	17.47 y
further information / internet-Links	
Internet-Link <ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	<p>http://www.siemens.com/snst</p>

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

5/11/2022 