# **SIEMENS**

## **Data sheet**

## 6GK1901-0DB20-6AA0

### product type designation

product description

### IE FC M12 Plug PRO (PROFINET)

M12 connector with high protection, 4-pole, D-coded

Industrial Ethernet FastConnect M12 plug PRO 2x2 M12 plug-in connector with rugged metal enclosure and FC connection method, with axial cable outlet (D-coded) 1 pack=1 unit for SCALANCE X208 PRO and ET 200 PRO PN.



suitability for use

For connecting electrical cables to SCALANCE X208PRO, ET200 PRO PN or ET200 eco PN for fast assembly with the FastConnect system

	•
transfer rate	
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s
interfaces	
number of electrical connections	
<ul> <li>for Industrial Ethernet FC TP cables</li> </ul>	4
<ul> <li>for network components or terminal equipment</li> </ul>	1
type of electrical connection	
<ul> <li>for Industrial Ethernet FC TP cables</li> </ul>	integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22
<ul> <li>for network components or terminal equipment</li> </ul>	M12 connector (D-coded)
type of electrical connection / FastConnect	Yes
mechanical data	
material / of the enclosure	metal
number of reuses	10
locking mechanism design	Screwed joint
tightening torque / for M12 round connector / maximum	0.6 N·m
connector coding / of the M12 circular connector	D
design, dimensions and weights	
type of cable outlet	180° cable outlet
width	19 mm
height	19 mm
depth	73 mm
net weight	40 g
connectable cable cross-section	6.5 6.5 mm
connectable conductor cross-section	0.33 mm²
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-40 +85 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
chemical resistance	
• to water	resistant
protection class IP	IP65/67

product feature	
PoE capability	Yes
PoE+capability	Yes
• silicon-free	Yes
product component	
• strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
<ul> <li>RoHS conformity</li> </ul>	Yes
UL approval	Yes
<ul> <li>cULus approval</li> </ul>	Yes
<ul> <li>railway application in accordance with EN 50155</li> </ul>	No
standard for structured cabling	Cat5
further information / internet links	
internet link	
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	http://www.siemens.com/tia-selection-tool
<ul> <li>to website: Industrial communication</li> </ul>	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter
<ul> <li>to website: Selection guide for cables and connectors</li> </ul>	https://sie.ag/2QdlxcP
to website: Image database	http://automation.siemens.com/bilddb
<ul><li>to website: CAx-Download-Manager</li></ul>	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com

last modified: 6/13/2021 **C**