

SITOP BATTERY MODULE/24V/12AH

SITOP battery module 24 V/12 Ah with maintenance free sealed lead batteries for SITOP DC UPS module 6 A, 15 A and 40 A *Ex approval no longer available*



Charging current charging voltage	
end-of-charge voltage at DC	
<ul style="list-style-type: none"> at -10 °C recommended at 0 °C recommended at 10 °C recommended at 20 °C recommended at 30 °C recommended at 40 °C recommended at 50 °C recommended 	29 V 28.4 V 27.8 V 27.3 V 26.8 V 26.6 V 26.3 V
Output	
charging current maximum	3 A
output voltage at DC rated value	24 V
Safety	
design of short-circuit protection	Battery fuse 20 A/32 V (solid-state circuitry blade-type fuse + support)
design of the overload protection	Valve control
Safety	
operating resource protection class	Class III
protection class IP	IP00
Approvals	
certificate of suitability	
<ul style="list-style-type: none"> CE marking UL approval as approval for USA cCSAus, Class 1, Division 2 ATEX 	Yes Yes cURus-Recognized (UL 1778, CSA C22.2 No. 107.1), File E219627 No No
certificate of suitability	
<ul style="list-style-type: none"> EAC approval shipbuilding approval 	Yes Yes
shipbuilding approval	ABS, DNV GL
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) DNV GL 	Yes Yes
environmental conditions	
Operating data note	For storage, mounting and operation of lead-acid batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed. You must ensure that the battery site is sufficiently ventilated. Possible sources of ignition must be at least 50 cm away.
ambient temperature	
<ul style="list-style-type: none"> during operation during transport during storage 	-15 ... +50 °C -20 ... +50 °C -20 ... +50 °C

relative temporary capacity loss at 20 °C in a month typical	3 %
Service life	
service life of energy storage	capacity falls to 80 % of original capacity (according to EUROBAT)
• typical	4 a
• at 20 °C typical	2 a
• at 30 °C typical	1 a
• at 40 °C typical	0.5 a
• at 50 °C typical	
ambient temperature during storage	Along with the storage and operating temperature, other factors such as the duration of the storage period and the charge status during storage have a decisive influence on the possible useful life. Batteries should therefore be stored as briefly as possible, always fully charged, and within the temperature range 0 to +20 °C.
Mechanics	
type of electrical connection	spring-loaded terminals
• for power supply unit	1 screw terminal each for 0.08 ... 4 mm ² for + BAT and - BAT
product component included	Accessories pack with solid-state circuitry fuse 20 A and 30 A
width of the enclosure	253 mm
height of the enclosure	168 mm
depth of the enclosure	121 mm
installation width	273 mm
mounting height	188 mm
fastening method	
• wall mounting	Yes
• standard rail mounting	No
• S7 rail mounting	No
fastening method	can be screwed onto flat surface (keyhole mounting for hooking in to M4 screws)
net weight	9 kg
number of cells	12
battery capacity	12 A·h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

