

Magnet coil for contactors 7.5 kW 24 V AC, 50 / 60 Hz, for motor contactors, Size S0, Screw terminal

General technical data	
Product brand name	SIRIUS
Product designation	Magnet coil
Control circuit	
Type of voltage of the control supply voltage	AC
Power loss [V·A] of magnet coil at AC typical	7.9 V·A
Control supply voltage	
<ul style="list-style-type: none"> • 1 at AC <ul style="list-style-type: none"> — at 50 Hz rated value — at 60 Hz rated value • 2 at AC <ul style="list-style-type: none"> — at 50 Hz rated value — at 60 Hz rated value 	24 V 24 V 24 V 24 V
Operating range factor control supply voltage rated value of magnet coil at AC	
<ul style="list-style-type: none"> • at 50 Hz • at 60 Hz 	0.8 ... 1.1 0.85 ... 1.1

Certificates/approvals			
General Product Approval	EMC	Declaration of Conformity	Shipping Approval



[Miscellaneous](#)



other

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2924-5AC21>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2924-5AC21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AC21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AC21&lang=en

last modified:

09/24/2019