

PS2 keyboard 19" INT, with touch pad, removable keyboard for devices with corresponding interface Further information, Quantity and content: see technical data



Figure similar

General information	
Product type designation	PS/2 built-in keyboard INT
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> <li>• Design</li> <li>• Keyboard assignment</li> <li>• Key illumination</li> <li>• Function keys                             <ul style="list-style-type: none"> <li>— Number of function keys</li> <li>— Programmable</li> </ul> </li> <li>• Number pad</li> <li>• Status LED displays                             <ul style="list-style-type: none"> <li>— for number pad</li> <li>— for Shift keys</li> </ul> </li> </ul>	Membrane keyboard B3F, 101/102 or 104/105 OMRON No 12 Yes Yes Yes; Num, Caps and Scroll Yes Yes
Connection type	
<ul style="list-style-type: none"> <li>• USB</li> </ul>	Yes; With PS/2 USB adapter (not included in the scope of supply)

• PS/2	Yes
<b>Frame size/design</b>	
• Standard	Yes; For industrial applications
<b>Installation type/mounting</b>	
Rack mounting	No; Built-in keyboard, 19" rack
<b>Input current</b>	
Current consumption (rated value)	25 mA; Typical
<b>Battery</b>	
Battery-operated	No; maintenance-free
<b>EMC</b>	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes
<b>Degree and class of protection</b>	
IP (at the front)	IP65
IP (rear)	IP20
Splashproof	Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
RoHS conformity	Yes
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	40 °C
Ambient temperature during storage/transportation	
• min.	-10 °C
• max.	50 °C
Relative humidity	
• Operation, max.	90 %; no condensation
• Condensation permissible	No
<b>Operating systems</b>	
Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 10	Yes
<b>Mechanics/material</b>	
Material	
• Sheet steel	Yes

Enclosure material (front)	Yes; AUTOTEX (R) V150
• Plastic	
<b>Service life</b>	
• Number of operating cycles, keys	1 000 000; Operations (minimum)
<b>Dimensions</b>	
Width	482.6 mm
Height	42.5 mm
Depth	177.8 mm
<b>Weights</b>	
Weight without packaging	1 480 g
Weight incl. packaging	1 665 g
<b>Scope of supply</b>	
Delivery quantity in pieces	1; Built-in keyboard rack mounting
<b>Other</b>	
Merchandise	Yes; TIPRO no. K-647 (K-847)
Manufacturer name	TIPRO Representative Office
Manufacturer's address	Vogelweg 20, 31785 Hameln, Germany
Target devices	Suitable for IPC and HMI devices with the corresponding interfaces (see manual)
Note:	Suitable PS/2 USB adapter (keyboard/mouse): 1x USB 1.1, plug A on 2x PS/2 sockets, 0.20 m, black; manufacturer: Renkforce; supply by Conrad Elektronik, order no.: 1360251 - 62
<b>Usable in the following products</b>	
• Product 1	<a href="#">6AV2124-0GC13-0AX0</a>
• Product 2	<a href="#">6AV2124-0QC13-0AX0</a>
<b>last modified:</b>	09/14/2020