

Contactor, AC-1, 4-pole, 800 A, main contacts 4 NO, Auxiliary contacts 2 NO + 2 NC, AC operation 110 V AC 50 Hz/120 V AC 60 Hz



Figure similar

Protection class IP on the front	IP00
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Reference code acc. to DIN EN 81346-2	Q
Reference code acc. to DIN EN 61346-2	Q
Number of poles for main current circuit	4
Number of NO contacts for main contacts	4
Number of NC contacts for main contacts	0
Operating current <ul style="list-style-type: none">• at AC-1 at 400 V<ul style="list-style-type: none">— at ambient temperature 40 °C rated value• at AC-3 at 400 V rated value	800 A 550 A
Operating power <ul style="list-style-type: none">• at AC-1 at 400 V rated value• at AC-3 at 400 V rated value	525 kW 280 kW
Type of voltage of the control supply voltage	AC
Control supply voltage at AC <ul style="list-style-type: none">• at 50 Hz rated value	110 V

Control supply voltage frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
Control version of the switch operating mechanism	conventional
Number of NC contacts for auxiliary contacts	2
• instantaneous contact	2
• lagging switching	0
Number of NO contacts for auxiliary contacts	
• instantaneous contact	2
• leading contact	0
Identification number and letter for switching elements	22
Mounting type	screw fixing
• Side-by-side mounting	Yes
Height	272 mm
Width	266 mm
Depth	225.5 mm
Type of electrical connection	
• for main current circuit	screw-type terminals
• for auxiliary and control current circuit	screw-type terminals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK1542-0AF0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK1542-0AF0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TK1542-0AF0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK1542-0AF0&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TK1542-0AF0/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TK1542-0AF0&objecttype=14&gridview=view1>

last modified:

09/23/2019