



Figure similar

MLFB-Ordering data

6SL3040-0JA01-0AA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Inputs / outputs

Digital inputs

Number	5
Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	6 mA
Delay time L→H, typ. ¹⁾	15 μs
Delay time H→L, typ. ¹⁾	55 μs

Fail-safe digital inputs

Number ²⁾	3
----------------------	---

Analog inputs

Number	1
Voltage	-10 ... +10 V
Resolution	12 bit + sign
Internal resistor	15 kOhm

Digital I/O

Number ³⁾	4
----------------------	---

As input

Voltage	-3 ... +30 V
Low level	-3 ... +5 V
High level	15 ... 30 V
Power consumption at 24 V DC, typ.	6 mA
Delay time L→H ¹⁾	5 μs
Delay time H→L ¹⁾	5 μs

As output

Continuous short-circuit proof	Yes
Voltage	DC 24 V
Load current per digital output, max.	100 mA
Delay time, approx.	150 μs

As fail-safe digital output

Number	1
--------	---

1) The specified delay times refer to the hardware. The actual reaction time depends on the time slot in which the digital input or output is processed.

2) 3 parameterizable, fail-safe digital inputs (floating), or alternatively 6 parameterizable digital inputs (floating)

3) can be parameterized - as DI - as DO



Figure similar

MLFB-Ordering data

6SL3040-0JA01-0AA0

Electrical data

Power supply voltage	DC 24 V -15 % +20 %
Max. power consumption ⁴⁾	0.8 A
Power loss, max.	20 W
Protection, max.	20 A

On-board encoder interface

Encoder evaluation optional incremental encoder TTL/HTL or encoder SSI without incremental signals

Current consumption at 24 V DC 0.35 A

Current consumption at 5 V DC 0.35 A

Encoder frequency, max. 500 kHz

SSI baudrate 100 ... 250 kBaud
The baud rate depends on cable length

SSI absolute position resolution 30 bit

Line length, max.

TTL encoder ⁵⁾	100 m (328.08 ft)
HTL encoder unipolar signal	100 m (328.08 ft)
HTL encoder bipolar signal	300 m (984.25 ft)
SSI encoder	100 m (328.08 ft)

Mechanical data

Dimensions

Width	73 mm (2.87 in)
Height	195 mm (7.68 in)
Depth	71 mm (2.80 in)
Net weight	0.95 kg (2.09 lb)

4) Power requirement 0.8 A for CU305 incl. 350 mA for HTL encoder + 0.5 A for PM340

5) TTL only bipolar signals; for bipolar signals, the signal lines must be twisted in pairs and shielded

Environmental conditions

Installation altitude 1000 m (3280.84 ft)

Ambient temperature during

Operation 0 ... 55 °C (32 ... 131 °F)

Storage -25 ... 70 °C (-13 ... 158 °F)

Transport -40 ... 70 °C (-40 ... 158 °F)

Relative humidity during

Transport, max. 95 %
at 40 °C (104 °F)

Connections

PE connection M5 screw

Supply voltage, max. 2.5 mm² (AWG14)

Digital inputs, max. 1.5 mm² (AWG16)

Digital inputs/outputs, max. 1.5 mm² (AWG16)

Communication

Communication PROFINET / EtherNet/IP

Standards

Compliance with standards cULus