## **SIEMENS**

## Data sheet

## 3RK1902-4GB50-4AA0

Control cable Pre-assembled at one end M12 socket angled 4-pole with 5 m cable 4 x 0.34 mm2 A-coded max. 4 A PUR sheath black



General technical data				
Product description		M12 lead, angled on one side		
Wire length	m	5		
General technical data				
Ampacity per pin maximum	А	4		
Operating voltage at DC maximum	V	250		
Surge voltage resistance rated value	V	2 500		
Mechanical data				
Type of connection		plugged, screwed		
Connector type	-	M12		
Connector coding of the M12 circular connector		A		
Number of electrical cores		4		
Type of cable outlet		angled		
Number of poles		4		
Color of cable sheath		Black		
Material of cable sheath		PUR		
Color of the insulation of data wires		see wiring diagram		
Material of the wire insulation		polypropylene (PP)		

Design of the shield		unshielded
Type of strain relief		cast
Outer diameter		
• of the cable	mm	4.7
• of inner conductor	mm	0.34
Type of connectable conductor cross-sections stranded		4 x 0.34 mm²
Type of plug interlock	_	M12 x 1 thread
Cable end components		open on one side
Ambient conditions		
Ambient temperature during operation		
• minimum	°C	-25
• maximum	°C	80
Protection class IP	_	IP67
Chemical resistance		
• to ASTM oil 2		conditional, must be checked relative to the application
● to mineral oil		conditional, must be checked relative to the application
• to water		conditional, must be checked relative to the application
• to grease		conditional, must be checked relative to the application
Degree of pollution		3
Certificates/ approvals		
Certificate of suitability		
CSA-approval		Yes
• UL approval		Yes
IEC certificate		Yes
Further information		

Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10

Industry Mall (Online ordering system)


https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1902-4GB50-4AA0

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1902-4GB50-4AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3RK1902-4GB50-4AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3RK1902-4GB50-4AA0&lang=en



1	brown/ braun (+)
	white/ weiss (NC)
2	blue/ blau (-)
3	black/ schwarz (NO)
4	

last modified:

03/14/2020