

SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2D/T, BU type A1,
Push-in terminals, without AUX terminals, New load group, WxH: 15x
117 mm, with temperature acquisition



General information

Product type designation	BU type A1
HW functional status	FS10 and higher

Supply voltage

Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic

Current carrying capacity

For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A

Hardware configuration

Temperature sensor	Yes
Formation of potential groups	
• New potential group	Yes
• Potential group continued from the left	No

Potential separation

between the potential groups	Yes
------------------------------	-----

Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	50 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
• for process terminals	CC00 to CC09
• for AUX terminals	does not exist
• for add-on terminals	does not exist
Connection method	
Terminals	
• Terminal type	Push-in terminal
• Conductor cross-section, min.	0.14 mm ² ; AWG 26
• Conductor cross-section, max.	2.5 mm ² ; AWG 14
• Number of process terminals to I/O module	16
• Number of terminals to AUX bus	0
• Number of add-on terminals	0
• Number of terminals with connection to P1 and P2 bus	2
Dimensions	
Width	15 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	40 g
last modified:	04/03/2020