



REPRESENTATIVE IMAGE

**Product:** [121872A](#)

DataTuff® Cat 6, 4 Bonded-Pr #23 Sol BC, PO Ins, PVC Jkt, AIA Armor, PVC Jkt, CMG CM

[Request Sample](#)

## Product Description

Industrial Ethernet Cat 6, 4 Bonded-Pair 23AWG (Solid) Bare Copper, PO Insulation, PVC Inner Jacket, Aluminum Interlock Armor, PVC Outer Jacket, CMG CM

## Technical Specifications

### Product Overview

|                        |                                                                                                                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc. exposure to rodent, crush, or cut through force,                                      |
| Patent:                | This product has one or more applicable patents. More information on patents can be found at <a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a> . |

### Construction Details

#### Conductor

| AWG | Stranding | Material         | Number of Pairs |
|-----|-----------|------------------|-----------------|
| 23  | Solid     | BC - Bare Copper | 4               |

#### Insulation

| Material        | Nom. Insulation Diameter | Color Code                                                                                                     |
|-----------------|--------------------------|----------------------------------------------------------------------------------------------------------------|
| PO - Polyolefin | 0.038                    | White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown |

|              |     |
|--------------|-----|
| Bonded-Pair: | Yes |
|--------------|-----|

#### Inner Jacket Material

| Material                 | Nom. Diameter    |
|--------------------------|------------------|
| PVC - Polyvinyl Chloride | 0.365 x 0.165 in |

#### Aarmor

| Armor Type & Material          | Diameter |
|--------------------------------|----------|
| AIA - Aluminum Interlock Armor | 0.625 in |

#### Outer Jacket Material

| Material                 | Nom. Diameter |
|--------------------------|---------------|
| PVC - Polyvinyl Chloride | 0.725 in      |

### Electrical Characteristics

#### Electricals

| Max. Conductor DCR | Max. DCR Unbalance | Max. Capacitance Unbalance | Nom. Mutual Capacitance |
|--------------------|--------------------|----------------------------|-------------------------|
| 93.8 Ohm/km        | 3%                 | 49.2 pF/ft                 | 17 pF/ft                |

#### Delay

| Max. Delay  | Max. Delay Skew | Nom. Velocity of Propagation (VP) [%] |
|-------------|-----------------|---------------------------------------|
| 510 ns/100m | 25 ns/100m      | 70%                                   |

#### High Freq

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Max./Min. Input Impedance (unFitted) | Max./Min. Fitted Impedance |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|--------------------------------------|----------------------------|
| 1 MHz           | 1.9 dB/100m                       | 74.3 dB        | 72.3 dB          | 72.4 dB       | 70.4 dB         | 67.8 dB                 | 64.8 dB                     | 20 dB                      | 100 ± 12 Ohm                         | 100 ± 15 Ohm               |

|           |              |         |         |         |         |         |         |         |              |          |
|-----------|--------------|---------|---------|---------|---------|---------|---------|---------|--------------|----------|
| 4 MHz     | 3.7 dB/100m  | 65.3 dB | 63.3 dB | 61.6 dB | 59.6 dB | 55.7 dB | 52.7 dB | 23 dB   | 100 ± 12 Ohm | 100 ± 15 |
| 8 MHz     | 5.3 dB/100m  | 60.3 dB | 58.8 dB | 55.5 dB | 53.5 dB | 49.7 dB | 46.7 dB | 24.5 dB | 100 ± 12 Ohm | 100 ± 15 |
| 10 MHz    | 5.9 dB/100m  | 59.3 dB | 57.3 dB | 53.4 dB | 51.4 dB | 47.8 dB | 44.8 dB | 25 dB   | 100 ± 12 Ohm | 100 ± 15 |
| 16 MHz    | 7.5 dB/100m  | 56.3 dB | 54.3 dB | 48.7 dB | 46.7 dB | 43.7 dB | 40.7 dB | 25 dB   | 100 ± 12 Ohm | 100 ± 8  |
| 20 MHz    | 8.4 dB/100m  | 54.8 dB | 52.8 dB | 46.4 dB | 44.4 dB | 41.7 dB | 38.7 dB | 25 dB   | 100 ± 12 Ohm | 100 ± 8  |
| 25 MHz    | 9.5 dB/100m  | 53.4 dB | 51.4 dB | 43.9 dB | 41.9 dB | 39.8 dB | 36.8 dB | 24.3 dB | 100 ± 15 Ohm | 100 ± 8  |
| 31.25 MHz | 10.6 dB/100m | 51.9 dB | 49.9 dB | 41.2 dB | 39.2 dB | 37.9 dB | 34.9 dB | 23.6 dB | 100 ± 15 Ohm | 100 ± 8  |
| 62.5 MHz  | 15.4 dB/100m | 47.4 dB | 45.4 dB | 32 dB   | 30 dB   | 31.8 dB | 28.8 dB | 21.5 dB | 100 ± 15 Ohm | 100 ± 8  |
| 100 MHz   | 19.8 dB/100m | 44.3 dB | 42.3 dB | 24.5 dB | 22.5 dB | 27.8 dB | 24.8 dB | 21 dB   | 100 ± 15 Ohm |          |
| 155 MHz   | 25.1 dB/100m | 41.5 dB | 39.5 dB | 16.3 dB | 14.3 dB | 23.9 dB | 20.9 dB | 21 dB   | 100 ± 15 Ohm |          |
| 200 MHz   | 29 dB/100m   | 39.9 dB | 37.9 dB | 10.8 dB | 10 dB   | 21.7 dB | 18.7 dB | 21 dB   | 100 ± 15 Ohm |          |
| 250 MHz   | 32.8 dB/100m | 38.3 dB | 36.3 dB | 5.5 dB  | 3.5 dB  | 19.8 dB | 16.8 dB | 18 dB   | 100 ± 20 Ohm |          |
| 300 MHz   | 35.2 dB/100m | 37.2 dB | 34.2 dB | 0.7 dB  | 0 dB    | 18.2 dB | 15.2 dB | 18 dB   | 100 ± 20 Ohm |          |
| 310 MHz   | 37.1 dB/100m | 36.9 dB | 34.9 dB | 0 dB    |         | 17.9 dB | 14.9 dB | 18 dB   | 100 ± 20 Ohm |          |
| 350 MHz   | 39.8 dB/100m | 36.2 dB | 34.2 dB |         |         | 16.9 dB | 13.9 dB | 17 dB   | 100 ± 22 Ohm |          |
| 400 MHz   | 43 dB/100m   | 35.3 dB | 33.3 dB |         |         | 15.7 dB | 12.7 dB | 14 dB   | 100 ± 32 Ohm |          |
| 500 MHz   | 49 dB/100m   | 33.8 dB | 31.8 dB |         |         | 13.8 dB | 10.8 dB | 14 dB   | 100 ± 32 Ohm |          |

Voltage

| UL Voltage Rating | Non-UL Voltage Rating |
|-------------------|-----------------------|
| 300 V (CM)        | 300 V (CMG-HL)        |

Mechanical Characteristics

Temperature

| UL Rating. | Operating      | Installation   | Storage        |
|------------|----------------|----------------|----------------|
| 60°C       | -40°C To +75°C | -25°C To +75°C | -40°C To +85°C |

Bend Radius

| Stationary Min. |
|-----------------|
| 8.25 in         |

|                    |                |
|--------------------|----------------|
| Max. Pull Tension: | 200 lbs        |
| Bulk Cable Weight: | 154 lbs/1000ft |

Standards and Compliance

|                                 |                                                                                                                |
|---------------------------------|----------------------------------------------------------------------------------------------------------------|
| Environmental Suitability:      | Indoor (Not Riser or Plenum), Indoor, Outdoor, Sunlight Resistance, Oil Resistance                             |
| Flammability / Fire Resistance: | UL 1685 (UL Loading), FT4, FT4, IEC 60332-1-2                                                                  |
| NEC / UL Compliance:            | 800, CM                                                                                                        |
| CEC / C(UL) Compliance:         | CMG, HL, CMG-HL                                                                                                |
| IEEE Compliance:                | IEEE 802.3bt Type 1, Type 2, Type 3, Type 4                                                                    |
| Data Category:                  | Category 6                                                                                                     |
| TIA/EIA Compliance:             | ANSI/TIA-568.2-D Category 6                                                                                    |
| CPR Euroclass:                  | Eca                                                                                                            |
| European Directive Compliance:  | EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| APAC Compliance:                | China RoHS II (GB/T 26572-2011)                                                                                |

Part Number

Variants

| Item #          | Color        | Putup Type | Length   | UPC          |
|-----------------|--------------|------------|----------|--------------|
| 121872A 0101000 | Black        | Reel       | 1,000 ft | 612825109037 |
| 121872A J221000 | Blue, Strong | Reel       | 1,000 ft | 612825109013 |
| 121872A 0081000 | Gray         | Reel       | 1,000 ft | 612825109020 |

Product Notes

|        |                                                                                                                                                                                       |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes: | US Patent #'s 5606151; 5734126; 5821467 **Values above 350 MHz are information only. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.383 Revision Date: 09-30-2020 |
|----------------------|--------------------------------------------------|

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.