



Product: GIGABIX CAT6+ PATCH CORDS ☑

GIGABIX CAT6+ Patch Cords

Product Description

GIGABIX CAT6+ Patch Cords

Technical Specifications

Product Overview

Physical Characteristics (Overall)

Total Number of Pairs:	4
Overall Nominal Diame	er: 0.221 in
Packaging:	Individually packaged in a clear plastic bag.

Connectors

Materials

Description	Material	
Boot	PVC	Black
Conductor	BC - Bare Copper	
Front Connection	Blades Phosphor Bronze with Tin Plating over Nickel	
Insulation	PO - Polyolefin	
Outer Jacket PVC - Polyvinyl Chloride		

Electrical Characteristics

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute		
Current Rating:	1.500 A		
Insulation Resistance:	500 M-Ohm Minimum		
Max Contact Resistance:	20 mOhm		

Temperature Range

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C

Mechanical Characteristics

Min Bend Radius (Overall Cable):	1.040 in
Footprint/Type:	GigaBIX
Plug /Jack Compatibility:	BIX

Termination Interface

Connection	Durabilities	
Mated Connection	200 Cycles	

Standards

UL Rating:	Riser
CSA Rating:	FT4
TIA/EIA Compliance:	Category 6 - TIA 568-C.2, ISO/IEC 11801:2002 Ed.2 Amendment 2

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	ACA, c(UL)us Listed

Related Part Numbers

Variants

	Item #	Color	Length	UPC
	AX101945		4 ft	611589003971
	AX101951		4 ft	611589004039
	AX101957		4 ft	611589004091
	AX101952		6 ft	611589004046
	AX101958		6 ft	611589004107
	AX101947		8 ft	611589003995
	AX101953		8 ft	611589004053
	AX101948		10 ft	611589004008
	AX101954		10 ft	611589004060
	AX101960		10 ft	611589004121
	AX101949		15 ft	611589004015
	AX101955		15 ft	611589004077
	AX101961		15 ft	611589004138
	AX101950		25 ft	611589004022
	AX101962		25 ft	611589004145
	AX101946	Black	6 ft	611589003988
	AX101959	Black	8 ft	611589004114
	AX101956	Black	25 ft	611589004084
	AX105559	Black	30 ft	611589113366
	AX105169	Black	50 ft	611589091220
	AX105170	Black	100 ft	611589091237
1				

History

Update and Revision:	Revision Number: 0.187 Revision Date: 03-04-2023
----------------------	--

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.