



Product: <u>3120A</u> ☑

DeviceBus® for InterBus®-S, 3 Pr #24 Str TC, PO Ins, OS+TC Brd, PUR Jkt, AWM 20233

Product Description

DeviceBus® for InterBus®-S, 3 Pair 24AWG (7x32) Tinned Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(90%) Shield, PUR Outer Jacket, AWM 20233

Technical Specifications

Product Overview

Suitable Applications:	harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.
DI : 101 / 101 / 10	

Physical Characteristics (Overall)

Conductor

AWG	Stranding	ng Material	No. of Pairs
24	7x32	TC - Tinned Copper	3
Condu	uctor Count:	nt:	6

Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.016 in

Color Chart

Number	Color
1	White & Brown
2	Pink & Gray
3	Yellow & Green

Outer Shield

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	1	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	24
Braid	2	Tinned Copper (TC)		90%		

Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness
PUR - Polyurethane	0.277 in	0.035 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
26 Ohm/1000ft	2.7 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield 15.4 pF/ft

Impedance

Nominal Characteristic Impedance

Delay

Nominal Velocity of Propagation (VP) [%] 66%

Current

Max. Recommended Current [A]
2.7 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	80°C
Operating Temperature Range:	-40°C to +80°C

Mechanical Characteristics

Oil Resistance:	Yes
Bulk Cable Weight:	54 lbs/1000ft
Max. Pull Tension:	33 lbs
Min. Bend Radius/Minor Axis:	3 in

Standards

UL AWM Style Compliance:	AWM 20233
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Sunlight Resistance: Yes

Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): No

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	UPC
3120A G7W500	Green, Matte	Reel	500 ft	612825141990
3120A G7W1000	Green, Matte	Reel	1,000 ft	612825141983
3120A G7W5000	Green, Matte	Reel	5,000 ft	612825142003

Footnote: C - CRATE REEL PUT-UP.

History

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.