



Product: <u>9740</u> ☑

Electronic, 1 PR #18 Str TC, PVC Ins, PVC Jkt, CMG

Request Sample

Product Description

Electronic, 1 Pair 18AWG (16x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

Technical Specifications

Product Overview

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	18 AWG	16x30	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.013 in (0.33 mm)	0.073 in (1.9 mm)	Black & Red

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter
F	PVC - Polyvinyl Chloride	0.032 in (0.81 mm)	0.210 in (5.33 mm)
C	Overall Cable Diameter (Nominal): 0.210 in (5.33 mm)

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	6.86 Ohm/1000ft	25.5 pF/ft (83.7 pF/m)	4.8 Amps per Conductor at 20°C

Voltage

UL Voltage Rating 300 V (CM), 300 V (UL AWM 2464)

Mechanical Characteristics

Temperature

UL Temperature	Operating		
80°C	-20°C to +80°C		

Bend Radius

Stationary win.	installation win.
2.1 in (53 mm)	2.1 in (53 mm)
Max. Pull Tension	on:
Bulk Cable Weig	ght:

Standards and Compliance

Environmental Suitability:	Indoor, Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 725, Article 800, CMG, CL3
AWM Compliance:	AWM 2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	89740, 87740, 82740

History

Update and Revision:	Revision Number: 0.526 Revision Date: 04-14-2023	

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC/EAN
9740 0601000	Chrome			612825257943
9740 060500	Chrome			612825257950
9740 0605000	Chrome			612825257967
9740 060U1000	Chrome			612825257929
9740.00305	Chrome	Reel	305 m	8719605022653

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.